CONFIDENTIAL 94/GS/TT Transportation, and Telecommunications **Brazil** September 1973 NATIONAL INTELLIGENCE SURVEY CONFIDENTIAL NO FOREIGN DISSE...

### NATIONAL INTELLIGENCE SURVEY PUBLICATIONS

The basic unit of the NIS is the General Survey, which is now published in a bound-by-chapter format so that topics of greater perishability can be updated on an individual basis. These chapters—Country Profile, The Society, Government and Politics, The Economy, Military Geography, Transportation and Telecommunications, Armed Forces, Science, and Intelligence and Security, provide the primary NIS coverage. Some chapters, particularly Science and Intelligence and Security, that are not pertinent to all countries, are produced selectively. For small countries requiring only minimal NIS treatment, the General Survey coverage may be bound into one volume.

Supplementing the General Survey is the NIS Basic Intelligence Fact-book, a ready reference publication that semiannually updates key statistical data found in the Survey. An unclassified edition of the factbook omits some details on the economy, the defense forces, and the intelligence and security organizations.

Although detailed sections on many topics were part of the NIS Program, production of these sections has been phased out. Those previously produced will continue to be available as long as the major portion of the study is considered valid.

A quarterly listing of all active NIS units is published in the *Inventory* of Available NIS Publications, which is also bound into the concurrent classified Factbook. The Inventory lists all NIS units by area name and number and includes classification and date of issue; it thus facilitates the ordering of NIS units as well as their filing, cataloging, and utilization.

Initial dissemination, additional copies of NIS units, or separate chapters of the General Surveys can be obtained directly or through liaison channels from the Central Intelligence Agency.

The General Survey is prepared for the NIS by the Central Intelligence Agency and the Defense Intelligence Agency under the general direction of the NIS Committee. It is coordinated, edited, published, and disseminated by the Central Intelligence Agency.

#### WARNING

This document contains information affecting the national defense of the United States, within the meaning of title 18, sections 793 and 794 of the US code, as amended. Its transmission or revelation of its contents to a receipt by an unauthorized person is prohibited by law.

CLASSIFIED BY 019641. EXEMPT FROM GENERAL DECLASSIFI-CATION SCHEDULE OF E. O. 11632 EXEMPTION CATEGORIES 58 (1), (2), (3). DECLASSIFIED ONLY ON APPROVAL OF THE DIRECTOR OF CENTRAL INTELLIGENCE.

# WARNING

The NIS is National Intelligence and may not be released or shown to representatives of any foreign government or international body except by specific authorization of the Director of Central Intelligence in accordance with the provisions of National Security Council Intelligence Directive No. 1.

For NIS containing unclassified material, however, the portions so marked may be made available for official purposes to foreign nationals and nongovernment personnel provided no attribution is made to National Intelligence or the National Intelligence Survey.

Subsections and graphics are individually classified according to content. Classification/control designations are:

(U/OU) Unclassified/For Official Use Only

(C) ..... Confidential

(S) ..... Secret

()

APPROVED FOR RELEASE: 2009/06/16: CIA\_RDP01\_00707R000200080021\_4 This chapter was prepared for the NIS by the Defense Intelligence Agency. It includes a contribution on airfields from the Defense Mapping Agency, Aerospace Center, and a contribution on merchant marine from the Department of the Navy. Research was substantially completed by May 1973.

# BRAZIL

# CONTENTS

This chapter supersedes the transportation and telecommunication coverage in the General Survey dated January 1970.

A. Appraisal	
B. Strategic mobility	
C. Railroads	
D. Highways	
E. Inland waterways	14
F. Pipelines	
G. Ports	
H. Merchant marine	
I. Civil air	
J. Airfields	
K. Telecommunications	33
Glossary	26
	JU

CONFIDENTIAL

No Foreign Dissem

# **FIGURES**

			Page			Page
Fig.	1	Highways in diversified terrain		Fig. 8	Rio de Janeiro and Santos, major	- uge
Fig.	9	(photos)	2		ports (photos)	24
rıg.	4	Rail-highway bridge over Rio Sao Francisco (photo)	7	Fig. 9	Major ports (table)	
Fig.	3	Selected rail lines (table)	8	Fig. 10	The Horta Barbosa, large tanker	
Fig.	4	Highways serving Sao Paulo (photos)	12		(photo)	29
Fig.		Selected highways (table)	15	Fig. 11	Selected airfields (table)	34
Fig.		Principal inland waterways (table)	18		Terrain and transportation	
Fig.	7	Principal pipelines (table)	21	-	(map) follows	36

# **Transportation and Telecommunications**

#### A. Appraisal (C)

The development of transportation (Figure 12) and telecommunication (telecom) systems in Brazil has been hampered by the great size of the area, unevenly distributed population centers, and a diversified terrain which in many places is unfavorable for highway and railroad construction (Figure 1). The overall inadequacy of the transportation and telecom facilities, most of which are located within a 300-mile belt paralleling the coastline, has been accentuated by an expanding economy and population.

Brazilian railroad and highway systems compare favorably with those of most other Latin American countries. The highway system, the most important means of domestic transportation, handles nearly 70% of all freight traffic. Railroads are used mainly for long-haul of bulk freight and commuter passenger traffic in the large cities.

Navigable waterways provide the major and often the only means of access to sparsely settled and underdeveloped sections, especially the vast western interior. In the east and south, waterways are important adjuncts to the rail and highway systems. The long coastline and the large number of population and economic centers along the littoral emphasize the importance of Brazilian seaports and merchant marine. Brazilian merchant ships handle the bulk of the coastal traffic, but a major share of the international cargoes, except for bulk petroleum, are carried in foreign-flag vessels. All the important ports, situated south of the "bulge," primarily serve their immediate geographic regions, which usually coincide with areas of densest population and greatest industrial and commercial activity. Most maritime activities are adequate for requirements of the economy. The petroleum pipeline system is confined to the industrialized and populated areas near the coast. Pipeline facilities are rapidly being expanded.

The civil air system provides good domestic and international service and to some extent compensates for the general inadequacy of surface transport by serving many areas not easily accessible by such means. Brazil's civil air fleet is one of the largest in the world.

Although it is underdeveloped, the rapidly expanding telecom system serves most population centers. The open-wire telephone network is gradually being replaced as the leading traffic carrier by the trunk radio-relay system. Domestic service is an oprovided by telegraph and radiocommunication networks. There are adequate wire, cable, and radio facilities for international communications.

Government ownership of transportation systems is concentrated in the railroads and merchant marine. Regulatory control over many facilities and modes is exercised through the Ministry of Transportation and Public Works and the Ministry of Air. Telecom facilities are owned and operated by the government and a number of private companies; responsibility for their operation is vested in the Ministry of Communications.

Development of the transportation systems is based on the government's 25-year National Transportation Plan, adopted in January 1965. The plan puts heavy emphasis and financial commitments on highway construction projects. It also provides for replacing old and obsolete equipment and facilities with new acquisitions. Improvements to the telecom system are based on a 10-year plan and emphasize expansion of the trunk radio-relay system and local telephone facilities. Lack of financial resources and planning problems are the principal barriers to completion of projects and goals.

There are several highway and railroad connections with Uruguay, one railroad to Bolivia, two highways to Paraguay, and one rail and one highway connection with Argentina. Waterway connections are made with nearly all neighboring countries by means of the Amazon River and Rio de la Plata¹ systems. Brazil lass numerous civil air and telecom connections with neighboring and other foreign countries

For diacrities on place names see the list of names on the apron of the Terrain and Transportation map and the map itself.



FIGURE 1. In opening up new territories, in this instance westward from Sao Paulo, Brazil is confronted with difficult terrain and tortuous roads and with plateaus over which it is possible to build highways having technical characteristics comparable to the best in the world (U/OU)



2

# B. Strategic Mobility (C)

The capability of transportation and telecom facilities to support major military movement and resupply operations varies from good in some areas to nearly impossible in the north and west. Most of the rail lines are located within a 300-mile belt paralleling the coarline in an area containing most of the major population centers and extensive agricultural, livestock, and mining industries. The rail network requires general repair and improvement but could support sustained military use. Three international rail connections are made with Uruguay and one each with Argentina and Bolivia; railroads serve all major ports.

Military traffic could move with ease on the relatively dense network of good roads in the east and south. However, there are only a limited number of good connecting routes between developed areas. Movement in underdeveloped regions would be restricted by the low density of roads, lack of alternate routes, and low construction standards that generally prevail. In rural areas, most surfaced roads have pavements of light construction and would require considerable maintenance effort if subjected to heavy military traffic.

0

Climate and terrain would also affect military movement via highways. Heavy rains caus, washouts, landslides, and flooding, often requiring extensive repairs. Unpaved roads are often impassable in the rainy season, and dusty at other times. The precipitous coastal escarpment limits movement inland. Sharp curves and steep grades prevail in the rugged highlands and deeply dissected plateaus. Much of the interior is covered by vast marshes and tropical rain forest. Because of the great number of streams the highways have many long bridges, which are vulnerable to interdiction. In mountainous areas, roads constructed along hillsides are highly vulnerable to hostile action because reconstruction is difficult or impossible. Roads in defiles are also vulnerable, but less repair effort is required to enable traffic to proceed over the rubble.

Inland waterways, including the Amazon, a complete system of transportation within itself, offer support to military operations in areas where other modes of transportation are undeveloped. In the east and south, waterways supplement the highway and rail system. Coastal ressels navigate the lower reaches of rivers which enter the Atlantic and on upper reaches of the Amazon and Rio de la Plata systems. Brazil has six major maritime ports and large numbers of smaller

ocean and inland waterway facilities. If the numerous dry-cargo ships were utilized, the merchant fleet has an extensive potential for short-haul (48 hours' steaming) troop lift and for logistics support of Brazilian military operations. The capability to support military operations over a protracted period at greater distances also is considerable. However, such military support potential could be diminished at the outset of an emergency by the unavailability of those ships engaged in international trade in distant waters. The military-lift and supply-transport capability of the 133 dry cargo ships and two combination passenger/eargo ships is about 781,800 carge deadweight tons. Of these ships, 39 have heavy-lift booms (40 or more tons), and 27 have large hatches (more than 50 feet in length). Three units have both large hatches and heavy-lift booms. Ships having service speeds of 18 knots or more number 30 (26 dry cargo and 4 refrigerator). The tanker fleet of 42 ships has an estimated lift capability of about 4,459,000 U.S. barrels of petroleum and related products. The 1,000-passenger total capacity of the two passenger ships could be increased considerably under emergency conditions.

The 2,411 airfields in Brazil are fairly well distributed and would be of considerable use in widespread military operations. The 30 major fields used by the Brazilian Air Force have a variety of aids such as instrument landing systems, area surveillance radar, VHF omni-directional range, and approach control towers; they also have refueling, meteorology, repair, and cargo-handling facilities. Airfields at Rio de Janeiro and Campinas can support heavy bomber operations; Augusto Severo, Brasilia, Campo Grande, Guararapes, Pinto Martins, and Val de Caes can support operations of jet fighters and medium to heavy bombers; and Campos dos Afonsos, Congonhas, Cumbica, Gravatai, Ponta Pelada, Salgado Filho, and Santa Cruz can support aircraft of 30,000 to 50,000 pounds. In an emergency the civil airfleet could significantly augment the Brazilian Air Force transport capability. A special unit of the air force is responsible for mobilizing civil aviation when the need

The improving telecom system would provide major support to military operations in the southern third of the country and in the coastal area. In the interior, unprotected open-wire lines, remote radio-relay sites, and lack of alternate routes contribute to a high vulnerability factor. Dense jungle and mountainous terrain severely limit the usability of wireline facilities.

#### C. Railroads (C)

The railroad network, the second largest in Latin America, is far superior in both extent and condition to the networks of all bordering countries except Argentina. However, it consists of a number of systems under different ownerships and having varying track gages. In addition, the network is hampered by uneconomic business practices and line locations. Consequently, the network is barely adequate for current needs.

Totaling 19,935 miles, the network consists predominantly of meter-gage (3'3'8") lines plus a limited mileage of 5'3" broad gage, standard gage (4'8'2"), and narrow gage less than 3'3'8". Efforts are being made to eliminate the few remaining miles of the narrowest gages. Distribution of the route mileage by gage is as follows:

GAGE	Route miles	PERCENT OF TOTAL
5′3″	2,085	10.5
4'8½"	121	0.6
3′3%″	17,586	88.2
Less than 3'3%"	143	0.7

Electrified lines total 1,621 miles and comprise, about 8% of the network. Power, which is drawn from the public net, is primarily 3,000-volt direct current, but there is some 1,500-volt and 600-volt direct current. All electrification uses overhead catenary and chiefly serves suburban areas of the large cities. The 455 miles of double track and 133 miles of multiple track are located primarily on electrified lines in the Santos, Sao Paulo, and Rio de Janeiro areas. Because of terrain, a section of line between Santos and Sao Paulo has funicular and rack rail.

Most rail lines are located within a 300-mile belt paralleling the coastline. The greatest density is in the southeast, and there are smaller concentrations in the far south and northeast. The area served by the railroads includes the major population centers and extensive agricultural, livestock, and mining industries. International connections consist of three with Uruguay and one each with Argentina and Bolivia. Except for the single-gage connection with Bolivia, all border crossings are made by short sections of dual-gage track.

The network consists of 26 rail systems, all of which are ultimately responsible to the Ministry of Transportation and Public Works through the National Railroad Department (DNEF). The 26 systems are owned, operated, or controlled by various administrations. The Federal Railroad Network, Inc. (RFFSA), a federal-government-controlled holding

company, controls 14 systems accounting for about 78% of the national route mileage. In 1968 the RFFSA systems were incorporated into four regions and 14 divisions. The regions are as follows:

Northeast Regional System (SRN) Central Regional System (SRC) South-Central Regional System (SRP) Southern Regional System (SRS)

All divisions are operating except the fourteenth. Its services were discontinued in early 1971 and all equipment and personnel were transferred to Division 11.

The Sao Paulo State Railroad Corp. (FEPASA), a state-government-controlled holding company, controls six rail systems accounting for about 17% of the total route mileage. Created in 1971, FEPASA incorporated the following systems:

Mogiana Railroad Company (CMEF) Paulista Railroad Company (CPEF) Araraquara Railroad (EFA) Campos do Jordao Railroad (EFCJ) Sorocabana Kailroad (EFS) Sao Pavlo and Minas Railroad (EFSPM)

The remaining six systems, accounting for 5% of the total route mileage and admini...tered by various government enterprises or private firms, are as follows:

Amapa Raifroad (EFAP)
Madeira Mamore Raifroad (EFMM)
Perus-Firapora Raifroad (EFPP)
Tocantins Raifroad (EFT)
Votorantim Raifroad (EFV)
Vitoria to Minas Raifroad (EFVM)

Because of competition from a paralleling highway, EFMM equipment is being shipped to Sao Paulo, and the track is to be dismantled.

Despite major track improvements, much of the meter-gage trackage is in only fair condition. Adequate for normal traffic, the trackage is not suitable for handling the heavier axle loads at higher speeds essential for efficient and profitable operation. The broad-gage trackage, though relatively small in extent, is in better condition. The standard-gage and less-than-meter-gage trackage is in poor to fair condition.

Track standards vary widely. Rail weights range from 64 to 115 pounds or yard on the broad gage, from 40 to 115 pounds on the meter gage, and from 25 to 50 pounds on the gages narrower than 3'3's"; all standard-gage rail weighs 90 pounds per yard. Most rail is of the standard T-section type. Eventually, most rail is to be welded, and welding plants are being constructed and used. Ties are spaced from 1,710 to

3,170 per mile and are primarily of untreated native hardwood or treated softwood. Steel and concrete ties are used on some RFFSA, FEPASA, and private lines and more are to be installed on new high-density lines. RFFSA plans to build a concrete-tie plant in the State of Pernambuco. Many ties are in fair or substandard condition, and ballast is generally poor because of improper maintenance. Crushed stone is the most widely used ballast and is usually laid to a depth of 6 to 12 inches; other materials used are gravel, sand, earth, and cinders. Maximum axleload limits range from 9 to 30 short tons. Except for 8% to 10.2% grades on the funicular and rack sections, the steepest grade is 4%. The minimum radius of curvature on main lines is 164 feet. Many lines in the southeast extend from the coastal area into the highlands and have numerous sharp curves and steep grades.

The rail network has over 6,000 bridges (each 16 feet or more in length) and over 200 tunnels. A 6,595-foot concrete rail-highway bridge over the Rio Paraguay at Porto Esperanca is the longest bridge; the longest tunnel, about 5 miles in length, is located between Lajes and Vacaria in southern Brazil. Most bridges are either of steel or reinforced-concrete construction, and tunnels are concrete lined.

Train movements are controlled primarily by the manual block system, but the use of centralized traffic control (CTC) and automatic block systems is increasing, particularly in suburban areas of large cities and on major new lines. Communications are primarily by telephone and telegraph; ho vever, RFFSA is installing teletype on major lines.

 $(\widehat{\cdot})$ 

Much of the rail network is located in mountainous or hilly terrain which adversely affects operations. Major natural traffic interruptions are floods, washouts, and landslides. The many operating problems, all of which are being studied and corrected, include: multiple, nonstandardized administrations, operating procedures, track gages, maintenance practices, and equipment; the lack of mechanization; existence of uneconomic lines; and poor track condition and alignment.

Because of recent purchases of motive power and rolling stock from Eastern and Western Europe, Japan, the United States, and domestic sources, the equipment inventory has become more adequate. Both archaic and ultramodern locomotives and rolling stock are in operation, and condition ranges from poor to excellent. Steam locomotives are quite old and are being phased out of service under continuing dieselization and electrification programs. Because of these programs, many diesel and electric locomotives are less than 10 years old. Most track maintenance

machinery has been purchased in the last 15 years; however, most is not yet used effectively.

Brazil is one of five Latin American countries producing rolling stock and one of three building locomotives. Additional rolling stock and an increasing number of locomotives are to be made in Brazil. Freight cars are being exported to Bolivia and Uruguay.

The 1970 equipment inventory for the entire rail network was as follows:

Locomotives:	
Steam	597
Diesel	1,508
Electric	246
Total	2,351
Railcars	461
Passenger cars:	
Coach	3,114
Pullman	280
Dining	193
Mail/Baggage	606
Miscellaneous	418
Total	4,611
Freight cars:	
Box	27,454
Gondola	15,093
Flat	6,705
Stock	3,584
Miscellaneous	6,546
Total	59,382

Wood, coal, fuel oil, diesel oil, and electricity are used for motive power. Only RFFSA locomotives use coal; RFFSA uses mainly electricity and diesel oil; FEPASA, mainly electricity. Nearly all coal and wood are obtained locally; some fuel oil and diesel oil supplies are imported. The 1970 motive-power fuel consumption was as follows:

	RFFSA	FEPASA	OTHERS	TOTAL
Wood (cu. yd.)	178,000	41,000	17,000	236,000
Coal (short tons)	33,605			33,605
Fuel oil (short				
tons)	84,423		862	85,285
Diesel oil (short				
tons)	252,052	61,708	62,756	376,516
Electricity (1,000				
kwhr.)	246,850	285,327	2,496	534,673

<sup>...</sup> Not pertinent.

Water generally is of excellent quality and the supply is adequate. In some areas, such as the northeast, seasonal drought conditions could affect the availability of water. There are no water treatment plants, but treatment compounds are used to a limited extent.

The most important of 15 major repair facilities are at Sao Paulo, Jundiai, Bauru, and Rio de Janeiro. Locomotives and rolling stock are repaired in all 15 shops, and maintenance is generally good. Most yard facilities are adequate to handle the traffic. The new hump yard at Sao Paulo has the track capacity to accommodate over 2,000 cars. Adequate transloading facilities are located at points where different gages meet. In 1971, FEPASA inaugurated Brazil's first truck-changing facility, at Porto Passagem.

Railroads are the principal long-distance bulkfreight carrier, but their share of the country's total freight movement is about 17% compared to 69% for highways and 14% for coastal maritime transport. Most suburban passenger traffic is via rail. In 1970 the rail lines carried a total of 83.6 million short tons of freight and accounted for 21 billion short-ton-miles. During the same period over 332 million passengers were carried and 7.7 billion passenger-miles were produced. Suburban lines transported 83% of the rail passengers. The general traffic pattern over the past few years indicates that freight traffic is increasing each year and passenger traffic is decreasing. The principal freight commodities hauled in 1970 were iron, coal, cement, coffee, corn, steel, sugar, wheat, gasoline, lumber, fertilizer, limestone, manganese, diesel oil, slag, and fuel oil. These commodities represented over 80% of the total volume of freight-car loadings; iron alone represented almost 46% of the total volume. In 1971, RFFSA began containerized freight shipments on a limited scale, and the line plans major usage of centainers between Rio de Janeiro and Sao Paulo. The regular rail shipment of automobiles between Sao Paulo producers and Rio distributors also began in 1971. An extensive Vitoria to Minas railroad modernization plan included installation of Brazil's first automatic car identification system.

Railroad income has not kept pace with rising costs, so the lines operate at a deficit, which is offset by subsidies paid by federal and state governments. The deficits, which are a large drain on the federal treasury, should decline because freight rates have been increased each year. In 1967, revenue for all the rail systems equalled about 49% of total expenditures; in 1969 the figure was 53%, and in 1970 it was 56%. The administrations are working to eliminate the deficits by 1975.

Most rairoads are overstaffed and some effort has been made to reduce the number of employees. Reductions totaled 15,000 between 1965 and 1967 and 11,500 between 1967 and 1569. Rail employment totaled 169,714 in 1970. Brazil has no organized trade schools, but employees receive on-

the-job training. In the past this has not produced highly efficient and competent workers, and efficiency and productivity are low. To ameliorate the situation, a massive training program began in 1971. Most employees belong to the National Federation of Railroad Workers, which is affiliated with the National Confederation of Land Transport Workers.

A 10-year railroad plan (1967-76) envisions eventual consolidation of all the railroads into one system based on four trunk lines, which are to radiate from Brasilia to the State of Rio Grande do Sul, to the State of Bahia and the north, to Beiem, and to Cuiaba. The national pattern is to be completed by 29 secondary trunk routes and 52 interconnecting lines.

The rail network is undergoing considerable change including discontinuing service on uneconomic lines; standardizing operating and administrative procedures, maintenance, equipment, and, eventually, track gages; mechanizing maintenance and freight handling; reducing overstaffing; adopting realistic freight rates and passenger fares; and applying modern business techniques. Extensive track-renewal projects provide for heavier loads, greater speeds, and more trains per day. Included are line relocations to achieve shorter distances, utilization of heavier rail, reduction of sharp curves and steep grades, and modernization and reequipment of facilities.

Important projects due for completion by 1980 are FEPASA's merger, reorganization, expansion, and eventual consolidation with RFFSA; completion of a rail-highway bridge (Figure 2) over the Rio Sao Francisco between Propria and Porto Real do Colegio to connect the northeastern and southern rail regions; completion of a Rio de Janeiro-Sao Paulo rapid-transit line; construction of a link between Sao Paulo and Belo Horizonte to provide direct access between Rio, Belo Horizonte, Brasilia, Sao Paulo, and Rio; completion of a southern trunk line to provide direct access between Rio Grande and Brasilia; completion of a rack-rail line on the Santos-Jundiai Division; completion of the Aguas Claras-Sepetiba ore line; further expansion of the Vitoria to Minas Railroad to double track; and completion of a rail beltway around Sao Paulo. Brazil is consulting with Paraguay regarding construction of lines to connect the two countries and with Bolivia regarding expansion of its lines. Brazil may offer financing for these new lines.

Replacing old equipment and increasing inventories are other important aspects of railroad improvement. Current equipment orders include more than 1,230 locomotives, 12 train sets, 22 railears, 8,750 freight ears, and 110 passenger ears. Brazil is to produce 112 locomotives, 3,192 freight ears, and 58 passenger ears.




FIGURE 2. Rail systems of northeastern and southern Brazil will be connected by this 2,763-foot rail-highway bridge over the Rio Sao Francisco between Propria and Porto Real do Colegio (U/OU)

Figure 3 lists selected characteristics of the major routes.

# D. Highways (C)

Highway transport handles about 69% of the total freight moved. However, because of the long distances and few alternative routes, the predominance of unsurfaced roads suitable only for light traffic, and poor original construction of important highways, the road network is inadequate for the growing needs of the country.

The highway system is unevenly distributed; nearly 75% of the road mileage is located within a 300-mile belt paralleling the coast from the border of Uruguay to the mouth of the Amazon River, and vast regions of the interior have no roads. The road density of Brazil, 0.18 mile of road per square mile of area, compares favorably with Argentina (0.12:1) and Venezuela (0.098:1). Brazil has six highway connections with Uruguay, one with Argentina, and two with Paraguay,

and construction projects underway are to provide one connection with Bolivia and one with Peru.

The highway network of about 591,000 miles consists of 32,000 miles of national highways, 75,000 miles of state highways, and 484,000 miles of provincial roads. The 31,000 miles of paved highways consist principally of bituminous and bituminous-treated surfaces. About 50% of the national system and 18% of the state roads are paved; provincial roads are predominately unsurfaced earth roads.

Surface widths on national and state highways range from 10 to 50 feet. The standard width for paved highways is 23 feet, but some sections range from 15 to 30 feet. Four-lane divided highways, usually with 23-foot-wide surfaces on each roadway, are located in the vicinities of Sao Paulo, Rio de Janeiro, Belo Horizonte, and Porto Alegre. Divided highways also connect Santos with Sao Paulo and Sao Paulo with Rio de Janeiro (Figure 4). The base course for bituminous and concrete surfaces is generally

FIGURE 3. Characteristics of selected rail lines (C) (3'3%", gage and single track except as noted)

		MAXIMUM GRADE	GRADE	MINIMOM		INTERVAL	
ORGANIZATION AND TERMINALS	MILES	Going	Coming	RADIUS OF CURVATURE	MAXIMUM	PASSING	REMARKS
Rede Ferroviaria Federal S.A. (RFFSA); Sistema Regional Nordeste (SRN); 1st Division—Maranhao-Piaui;		Percent	lu	Feet	Short tons	Miles	
Sao Luis-Teresina	281	3.5 (Direction na)	n na)	581	na	16	Diesel and steam cperated.
Teresina~Luis Correia	213	1.6	na	427	na c c:	<del>1</del>	
Fortaleza-Oiticica	311			#00°	7.61	20	Diesel operated.
Camocim-Sobral	80	:	:			11 8	
3rd Division Nordeste (Northeast)	60e	*3.5		*328	13.2	<b>5</b> :	Diesel and steam operated. Some steel ties on
Recife-Nata	989					:	division.
Cabedelo-Paula Cavalente	333				:	<u>:</u> 2	
Itabaiana-Mossoro	395				:	3 5	
	378			:	:	; -	
Recife-Maceio.	216				:	: =	
Rio Largo-Porto Real do Colegio	167		:	:	:	7	Rail-highway bridge under construction to Propria
							across Rio Sao Francisco; rail ferry used in interim.
4th Division—Leste (East):							
Salvador-Propria	343	1.5 (est.) (Direction na)	on na)	328	па	22	Diesel, electric, and steam operated. Double track to MP 8; electrified to Magoinhas (MP 77). Railhighway bridge under construction to Porto Real do Colegio aercas Rio San Francisco; rail ferry used in interim
Mapele-Monte Azul	531	3.6	:	361	иа	25	Diesel, electric, and steam operated. Electrified to
		(Direction na)	n na)				Santo Amaro (MP 35).
Sao Francisco-Paulistana	406	na	na	nu	na	21	Diesel and steam operated.
Angra dos Reis-Goiania	911	ec ::- :e	3.2 (est.)	312	ри	24	Diesel, lectric, and steam operated. Electrified (1,500- and 3,000-v.d.c. overhead catenary) for 216 miles Lidice (MP 28)—Lavras (MP 244); dual gage (37334" and 26") 9 miles Lavras-

Roncador-Brasilia	3	0.°	9.5	361	na	13	Diesel, electric, and steam operated. Electrified 97
	55	9		361	;	9	miles Divinopolis (MP 88) Belo Horizonte.
6th Division-Central	201	7.	1.1	1,120	มส	+3	Diesel and steam operated.
Rio de Janeiro-Monte Azul.		Remarks	Remarks	Remarks	па	50	5/37 and 3/334/7); 5/37 gage; 32 miles dual gage (5/37 and 3/334/7); Paraiba do Sul (MP 117)-Fernandes Pinheiro (MP 127); Conselheiro Lafaiete (MP 288)- Doutor Joaquim Murtinho (MP 297); Ferrugem (MP 388)-Horto Florestal (MP 401), Double or multiple track to Barra do Pirai (MP 68); slee- trified to Tres Flox (MP 123) and Re: and AP
Barra do Pirai-Sao Paulo	243	0.5 (Direction na)	ion na)	2,230	па	∞	381)-Belo Horizonte (MP 389). To Conselheiro Lafaiete maximum grade is 2.3% (direction na.), minimum radius of curvature is 377 ft. 573" gage. Electrified to Barra Mansa (MP 28) and Mogi daz Cruzes (MP 212)-Suo Paulo, latter 31 miles double track. Construction of high-speed line by Isonasse under construction of high-speed
7th Division—Leopoldina	:	:	:	:	22.0	:	usage of concrete ties on line.  Diesel and steam operated. Some steel ties on
Rio de Janeiro-Vitoria	396	9	3.0	569	:	61	division.  Multiple track, including electrified track to Duque to Caxias (MP 19) which is concepted by 6th
Rio de Janeiro-Caratinga	419	3.7	3.3	164		19	division only.
Tres Rios-Manhuacu Sistema Regional Centro-Sul (SRP):	247	Remarks	Remarks	Remarks		15	Recreio (MP 82)-Manhuacu (MP 247) maximum grade going is 2.6%, coming 3.0%, minimum radius of curvature is 249 ft.
Santos-Jundiai	95	8.0 and 10.2	:	1,146	. 8 . 8 . 8	∞	5/3" gage. Electric, diesel, and steam operated. Double track except for about 6 miles of multiple track in Sao Paulo area. Electrified Paranapiacaba (MP 19)-Jundiai. Funicular or cable-operated Piassaguen (MP 12)-Paranapiacaba; electrified rack RR. under construction to supplement funicular section.
loth Division—Noroeste (Northwest): Bauru-Corumba	821	1.0	on na)	3,281	Remarks	60 ##	Diesel and steam operated. Maximum axleload 19,8 short tons for diesel, 17.6 short tons for steam.

(

(المستنبين)	
Ç	
ine	
Ē	
Selected	
ţ	
Characteristics	
က	
FIGURE	

10

		MAXIMU	MAXIMUM GRADE	MINIMEM		MAXIMUM INTERVAL BETWEEN	
ORGANIZATION AND TERMINALS	ROUTE	Going	Coming	RADIUS OF CURVATURE	MAXIMUM AXLELOAD	PASSING TRACK	REMARKS
Sistems Beniand Col (CDC).		Per	- Percent	Feet	Short tons	Miles	
Itarare-Marcelino Ramos	536	ες. ε <u>ς</u> .	па	295	22.0	13	Diesel and steam operated. Section of newly inaugurated Southern Trunk providing shorter
Paranagua-Ponta Grossa	167	Remarks	Remarks Remarks	Remarks	:	=	rail route to Sao Paulo-Rio de Janeiro-Brasilia area and N. Diesel, electric, and steam operated. Electrified 32 miles Veu da Noiva (MP 41)-Porton (MP 73). Newly, reconstructed soution, Prenabilia, plan
Engenheiro Bley-Lajes	231	1.3	:	1,129		<u>e</u>	(MP 116)-Ponta Grossa has maximum grade of 1.0%, minimum radius of curvature of 1.644 ft.; this section forms part of newly inaugurated Southern Trunk (see above).  Dissel and steam conserve.
Sao Francisco do Sul-Porto União	260	(Direct	(Direction na)	221		! <b>;</b>	inaugurated Southern Trunk (see above).
12th Division-Teresa Cristina:	}	?	•	100		9	Diesel and steam operated.
Imbituba-Ararangua 13th Division—Rio Grande do Sul	06	0.1*		*328	9.71	6	Steam operated.
Porto Alegre-Uruguaiana	91+	6.8*		*410	19.8	13	Diesel and steam operated.  At Uruguaiana dual-gage track (3/33/8", and 4/81/2")  crosses. Rio. Uruguai vio. international
General Luz-Lajes	247	1.5	: 1	1,004	:	na	highway bridge to Paso de los Libres, Argentina. Section of newly inaugurated Southern T: unk (see
Santa Maria-Marcelino Ramos	320	(Direction na)	ion na)			91	above), containing long tunnels and bridges.
Rio Grande-Cacequi	298					<u>°</u> ∞	
Basilio-Jaguarao	69	:	:		:	14	Dual-gage track (3'33'8" and 4'81'2") crosses Rio Jaguarao via international rail-highway bridge to
Entroncamento-Santana do Livramento	86	:	:	:	: : :	22	rto Branco, Uruguay: transloading facilities at both stations.  Dual-gage (3.3%, and 4/81/2/) connection at Santana do Livramento with Rivers Universe.
Alegrete-Quarai	52	:	:	:	:	15	transloading facilities at both stations.  Dual-gage track (3/39/8" and 4/81/2") crosses Rio
							Quarai via international bridge to Artigas, Uruguay; transloading facilities at Quarai and

()

0


	26 Diesel and steam operated.	5'3", gage. Diesel, electric, and steam onerated	Some steel ties used in CPEF network  11 Double track to Campinas (MP 28): electrified to	Rincao (MP 178). 43 Electrified to Cabralia Paulista (MP 129).	19 5'3" gage. Diesel operated.	Diesel and electric operated.  11 Double track to Ipero (MP 87): electrified to	Rubiao Junior (MP 171). To MP 87 minimum radius of curvature is 1,146 ft.  9 Electrified to Itapetinings (MP 37).  14 Electrified to Ibirarema (MP 137).	Diesel operated.  17 Line carries heavy mineral ore traffic.  14 Pual gage (3/33/8" and 5/3") for last 3 miles.
	20.9	26.4	:	:	30.8		: : : : : : : :	26.4 na
	382	*988	3,760		2,604	*785 19.8		663
	1.5	0.5*	0.1	(Direction na)	1.0	*2.1		1.0 0.5 na na
	61+1	:	315	332	268	242	165 357	337
Ferrovia Paulista S.A. (FEPASA): Companhia Mogiana de Estrada de Ferro (CMEF);	Campinas-Araguari	Companhia Paulista de Estra la de Ferro (CPEF)	Jundiai-Colombia	Itirapina-Panorama Estrada de Ferro Araraquara (EF.4):	Araraquara-Rubineia	Estrada de Ferro Sorocabana (EFS)	Ipero-Itarare.  Botucatu-Presidente Epitacio.  Diverse Administrations:  Estrada de ferro Vitoria a Minas (EFVW)	

NOTE—Unless specified, electrification is 3,000-v. d.c., overhead catenary.

nu Date not avilable.

\*Maximum grade or minimum radius of curvature for pertinent division or system. Specific line grades and grade direction na.





Highway through rugged terrain between Sao Paulo and Santos

Four-lane highway between Sao Paulo and Rio de Janeiro

FIGURE 4. Highways serving Sao Paulo (U/OU)

crushed stone and ranges in thickness from 3 to 27 inches. Shoulders are from 3 to 16 feet wide and are usually gravel, stone, or earth; on some sections they are bituminous surface treated.

Brazilian highway design standards vary. A minimum radius of curvature of 100 feet is permitted on low-class roads in mountainous terrain, but a 1,870-foot radius is required for high-class roads in flat terrain. Maximum grades vary from 3% to 8%. Construction standards are usually enforced for new projects, especially those financed by international lending agencies.

More than 55% of the highway bridges are constructed of reinforced concrete, and most of the remainder are of timber or masonry; there are very few steel bridges. Concrete beam is the principal structural type for spans of 100 feet and under, and concrete arches of the open-spandrel type are most commonly used for longer bridges. Standard concrete highway bridges are designed to support a column of 24-ton loads or a 34-ton single load. Most bridges on federal highways are in good condition. Timber bridges on many roads throughout the country are in various stages of deterioration.

The 20 tunnels on the highway system, which are located near Ri > de Janeiro and Sao Paulo, are concrete lined, ventilated, and in fair to good condition. The numerous fords are on state highways and local roads or on pioneer federal highways. There are about 500 ferry crossings.

Within the Ministry of Transportation and Public Works a permanent government agency known as Grupo de Estudas Para Integração de Política de Transports—GEIPOT is responsible for planning and advising the minister on national transport. Its duties include coordinating and integrating transport policy with the national economic and social plans.

The National Highway Department (DNER), under the Ministry of Transportation and Public Works, administers the national highway network. Maintenance and construction are accomplished through 20 district offices. In each state is a state highway department (DER) responsible for its highway network. Government policy is to transfer maintenance and construction functions gradually from DNER to the DER's, thus enabling DNER to concentrate on planning and overall supervision. Maintenance operations are performed by the national and state highway department personnel and by contract. Most construction projects are accomplished by private contractors, but some is done by army engineers, especially in remote areas.

O

Highway construction and maintenance operations are hampered by heavy rains which cause floods, landslides, and cave-ins, sometimes necessitating extensive repairs. Terrain obstacles include the precipitous coastal escarpment, rugged highlands, deeply dissected plateaus, vast marshes, jungles, and dense forest. A shortage of modern equipment for mechanized road operations is being alleviated through loans and planning.

There are adequate domestic supplies of portland cement, stone, gravel, timber, and asphalt. However, much of this material must be transported great distances. Some steel and a few types of construction equipment are produced domestically, but most equipment is imported from the United States, Western Europe, and Japan. Imports include dump trucks, graders, bulldozers, compaction machines, and asphalt mixers and spreaders.

Large increases in transport volumes, both in passenger and freight, have resulted in pressures to improve and extend the highway network. The basis for all highway development is the 25-year National Transport Plan, adopted in 1965 and updated periodically. DNER continually reviews the program to ensure that established priorities are currently valid. Revenues from road-user taxes cover about 70% of the cost of construction, maintenance, and administration; the remainder is borrowed from international financing organizations.

Among the more important projects are the Central-West Development Program and the Program for the Sao Francisco Valley. The Central-West Development Program encompasses the States of Mato Grosso and Goias and calls for building 1,000 miles of basic roads and paving 1,300 miles more in a region which has a huge economic potential and occupies an important area for agricultural expansion. The Sao Francisco Valley program calls for building 1,000 miles of basic roads and paving another 1,000, thus assuring this area of more favorable conditions for producing and circulating its wealth.

In addition to these first-priority projects, reconstruction and improvement are nearing completion on two major north-south highways, both of which are over 2,000 miles in length. The inland route connects Jaguaribe, on the Uruguay border, to Fortaleza, in the northeastern State of Ceara. The other route runs along the coast and links Osorio, in Rio Grande do Sul, to Natal, in Rio Grande do Norte. Both roads interconnect Brazil's major cities.

The highway plan for development of the Amazon calls for constructing, by 1974, some 10,000 miles of roads, 2,200 of which will be paved. The most spectacular of these projects is the Trans-Amazonian Highway being constructed from Joao Pessoa and Recife on the Atlantic coast to the Peru border. Major projects scheduled for completion by 1975 include improving the road from Brasilia to Porto Velhe via Cuiaba; surfacing the newly completed road from Manaus to Porto Velho, building a road from Santarem to Cuiaba; and paving the road from Belem to Brasilia.

Traffic is interrupted on highways in hilly and mountainous eastern Brazil by landslides, rockslides, and washouts, and in the rest of the country by the effects of flooding during heavy rainfall, which occurs generally from September through May for most of the country. Earth roads are often impassable during the rainy season. In some locations on federal highways, and more commonly on state highways and local roads, use of fords and ferries is restricted. Traffic flow is impeded on secondary and tertiary roads by narrow timber bridges, and in hilly and mountainous regions by steep grades and sharp curves.

Highway transport firms are privately owned, and most freight and passenger operations are performed by one-vehicle owners. A great amount of trucking is accomplished by farmers, ranchers, manufacturers, and service industries. Several large bus companies operate in the larger metropolitan areas, and numerous small lines serve the smaller towns.

Users are free to select the mode of transport which best suits their requirements. Entry into the interstate road transport industry requires DNER approval, but granting of licenses is almost automatic. Intrastate trucking operations are licensed by the DER's in the same way. Bus companies must apply to DNER or to DER's, prove proble need, and file tariffs and timetables for each route.

Highway freir, ht traffic grew by about 11% each year during the sixties and increased its share of the total freight movement from 62% in 1961 to 69% in 1970. For the same period the highway share of passenger traffic rose from 74% to 91%. The principal goods hauled are coffee, farm produce, processed foods, and lumber. In addition, large quantities of other building materials and machinery are moved along the highways.

In 1970 the inventory of 3,451,000 vehicles consisted of 2,694,000 passenger cars, 59,000 buses, and 698,000 trucks, including pickups and vans.

Vehicle production is growing at the rate of 20% a year. Over 500,000 vehicles were produced in 1971, and a capacity of 1 million vehicles per year is expected to be achieved by 1975. Brazil is self sufficient in the production of passenger cars. Trucks, buses, construction machinery, and spare parts are also produced, but some are also imported.

Figure 5 lists characteristics of selected highways.

# E. Inland waterways (C)

Brazil's major inland waterways are the Amazon, the Rio Sao Francisco, the Lagoa dos Patos, the Rio Parana, the Rio Paraguay, and the Uruguay. With their tributaries they are navigable for a total of about 31,000 miles and provide the principal surface routes of transportation and communication through extensive sparsely settled and generally undeveloped or otherwise inaccessible sections of the country. The principal commodities shipped are timber, nuts, cocoa beans, mate, bituminous coal, and various mineral ores. Trends point to increased utilization of the waterways as arteries of freight and passenger transportation in the future.

The inland waterways may be divided geographically into the following general groups:

Northwestern group:

Rio Araguari	Rio Madeira
Amazon	io Purus
Rio Negro	Rio Tocantins
Northeastern coastal group:	
Rio Para	Rio Itapicuru
Rio Gurupi	Rio Parnaiba
Rio Turiacu	Rio Acu
Rio Mearim	Rio Paraiba
Eastern group:	
Rio Sao Francisco	Rio Mucuri
Rio Paraguacu	Rio Doce
Rio Pardo	Rio Paraiba do Sul
Rio Jequitinhonha	
Southeastern coastal group:	
Rio Itajai	Rio Jaguarao
Lagoa dos Patos-Rio Guaiba	Rio Iguacu
Rio Jacui	Rio Tiete
Lagoa Mirim-Canal de Sao Goncalo	
Southern and Southwestern groups:	
Rio de la Plata	Rio Parana
Unionav	Rio Paraguay

The Amazon River system, with its tributaries, provides Brazil with over 20,000 miles of seasonally navigable waterways; standard oceangoing cargo vessels ascend to the port of Manaus on the Rio Negro, about 1,100 miles from the Atlaatic mouth. Significant among the national government's plans for Amazon Basin development is a project to expand Santarem into a deepwater port. Santarem lies at the junction of the Amazon and the Rio Tapajos and is the starting point of a transjungle highway to Cuiaba, about 1,000 miles southward, on a Rio Paraguay tributary.

Of the northeastern coastal waterways, the Rio Parnaiba, potentially the most important, has the longest extent of navigability, about 680 miles. Navigation locks under construction at the Boa Esperanca hydroelectric dam will increase the navigability of the Rio Parnaiba and facilitate transportation to the central and eastern parts of the country. Navigability of the other streams in the northeast area varies from 11 miles to 300 miles.

in the eastern area, the Rio Sao Francisco is navigable for about 1,000 miles, serving a valley of several hundred thousand square miles; portions totaling about 800 miles are being dredged and regulated to eliminate shallows, waterfalls, and rapids. A new river port is planned at Pirapora, in the State of Minas Gerais, near the headwaters of the Rio Sao Francisco where it approaches the Pan American Highway leading into the new Brazilian capital of Brasilia. Most of the other eastern waterways are short,

_
Ü
_
shways
Ë
cted
Sele
Ś
SUR E
ಠ

ORIGIN AND DESTINATION	DISTANCE	SURFACE TYPE	SURFACE WIDTH	SHOULDER	HEMARKS
Uruguay border near Chui to Rio de Janeiro via Porto Alegre, Curitiba, Sao Paulo.	Miles 1,298	Bituminous	Feet Mostly 21 to 23 (see remarks)	Feet 3 to 10	Sao Paulo-Rio de Janeiro route is 4 lanes wide, many segments consisting of 2 roadways divided by median
Uruguaiana to Porto Alegre.  Foz do Iguacu to Curitiba. Sao Paulo to Brasilia.  Rio de Janeiro to Brasilia via Belo Horizonte.  Road junction 85 miles N. of Rio de Janeiro to Salvador	408 420 715 785 940	do	23 23 20 to 25 20 to 25	6 3 to 6 3 to 10 4 to 10 4 to 6	strip. First 60 miles is a 4-lane divided highway. First 70 miles is a 4-lane divided highway.
Belem to Brasilia.	340 (approx.)	Remarks	Remarks	na	Originally completed in 1959 as unpayed "pioneer" road, 26 ft. wide, with Sharp curves, steep grandes, single- lane timber bridges. Road now, bains second
na Data not available.					with improved alignment, 2-lane bituminous pave- nient, 2-lane concrete bridges. Completion e-heduled for 1975.

swift-flowing streams with navigability ranging from 50 to 75 miles.

The most important and most developed waterway in Brazil is the 166-mile-long Lagoa dos Patos-Rio Guaiba in the southeastern part of the country; it carries a greater volume of traffic than any other waterway. With the ocean ports of Porto Alegre and Rio Grande at the northern and southern ends of Lagoa dos Patos, respectively, this waterway provides an outlet for the rich wheat- and cattle-producing region known as the "bread basket" of Brazil. Lagoa Mirim-Canal Sao Goncalo, with 158 miles of navigability, serves both Brazil and Uruguay. The other streams in the southeast have from 17 miles to about 500 miles of navigability. The Rio Guaiba has been improved with dams and locks and accommodates large river steamers for a distance of 177 miles. The Rio Tiete and the Rio Jacui are under extensive development. A project has been undertaken to connect the Rio Ibicui, a tributary of the Uruguay. with the Rio Jacui by means of a 95-mile-long canal, providing the State of Rio Grande do Sul with an eastwest waterway.

In southern and southwestern Brazil, the Rio de la Plata system is dominant. The Uruguay and its tributaries provide about 1,250 miles of navigable routes; its upper reaches form most of the boundary between Brazil and Argentina. The Uruguay is navigable most of the year for about 700 miles within Brazilian territory where it is utilized in the transport of agricultural products to railroad centers along the river and in the rafting of timber downstream.

The Rio Parana, main artery of the Rio de la Plata system, forms part of the boundary between southeast Paraguay and Brazil. The upper third of the Parana, known as the Alto Parana, lies mostly within Brazil; two sections, roughly 80 miles and 300 miles long, are navigable. The nonnavigable portion between these two sections includes Salto das Sete Quedas, giant waterfalls at Guaira on the Paraguay border. Waterborne operations on the lower 80-mile section are made difficult by aumerous rapids and dangerous whirlpools. Navigation locks are under construction on the Alto Parana. The chief cargo carried on the Brazilian portion of the Rio Parana consists of forest products and verba mate.

The Brazilian section of the Rio Paraguay forms part of the border with Bolivia and is navigable for over 600 miles except during the low-water period, from November to February. Corumba, on the Rio Paraguay just across from the extreme southeastern part of Bolivia, lies about 150 miles upstream from the Paraguay border. The center of most of the area's

commercial activity, Corumba is concerned with the transport of agricultural and mineral products and general merchandise in domestic and international trade. The Rio Paraguay also serves as an outlet for Bolivian products. Ladario, roughly 20 miles east-southeast of Corumba, is the site of a small naval installation where the Mato Grosso Flotilla is based. A drydock here is operational only in the rainy season.

Of the major inland waterways, the southeastern group carries about 65% of the cargo volume and the Amazonian group almost 20%.

The waterways of Brazil are navigable by a variety of craft. Many of the streams entering the Atlantic are capable of carrying standard ocean-type cargo vessels considerable distances inland. Manaus, Belem, and Sao Luis are served by such vessels as are the coastal ports of Rio Grande and Pelotas in southern Brazil. Coastal-type vessels navigate throughout the lower reaches of most coastal streams entering the Atlantic Ocean directly and on the upper reaches of the Amazon and the Rio de la Plata systems. River craft utilize the middle and upper reaches of most navigable streams in Brazil. Small native craft ply the upper reaches of the coastal streams as well as the tributaries of the Amazon, the Rio Sao Francisco, and the Rio de la Plata systems.

Navigation is interrupted by silting, rapids, falls, and floating debris. Sandbars and other obstructions formed by sediment and debris during high water often interrupt or limit navigation when flood waters recede. Rapids constitute seasonal interruptions in many of the waterways and permit only sectional navigation in others.

Structures on the inland waterways include bridges, overhead and submarine cables, navigation locks, and an increasing number of dams. Most new dams include plans for Eavigation locks. There are about 80 bridges over the Eavigable waterways, probably the most important being the international highway structure over the Rio Parana at Foz do Iguacu between Brazil and Paraguay.

The more than 700 ports and landings situated on the inland waterways range from maritime ports to small landings at villages in remote interior areas. Craft operating on the waterways include a large portion of the Brazilian merchant marine, privately owned river craft, and foreign-flag vessels operating in Brazil. A greater volume of cargo is handled by privately owned nonsubsidized companies than by the large federally controlled river services. The principal river service in the Amazon Basin is provided by the federally subsidized Navigation Services of the Amazonian Region and Administration of the Port of

Para (Belem), which has a fleet of over 100 units, including modern cargo-passenger vessels, paddlewheel steamers, tugs, barges, and launches. The Rio Sao Francisco fleet includes 15 river steamers, about 50 diesel-powered barges, numerous manually propelled barges, and a number of cargo vessels of 20 to 30 tons carrying capacity. On the Lagoa dos Patos system, 20 companies provide service, including nine that have a combined fleet of over 100 craft that operate on the Rio Taquari and Rio Jacui. Service on the Rio Paraguay is provided by the government subsidized Navigation Service of the Prata Basin, which has a fleet of tugs, barges, river steamers, and other miscellaneous craft. Many of the craft are obsolete, and the fleet is generally inadequate. Coastal vessels also operate on the inland waterways, chiefly on the Amazon and Lagoa dos Patos systems.

A Presidential Decree of 1966 placed control of the inland waterways under the National Department of Ports and Navigable Routes (DNPVN), a dependency of the Ministry of Transportation and Public Works. The DNPVN has two groups concerned with waterways, the Directorate of Navigable Routes and the National Institute of Water Routes Investigations. Regional Directors act as field representatives for the National Director.

0

Developmental policy for inland waterways originates from the Ministry of Transportation and Public Works. Numerous federal and state improvement programs that have been implemented include canalizing important streams; rehabilitating ports, some of which are to have specialized terminals for handling regional agricultural and mineral produce; expanding shipyards and ship-repair centers; and replacing antiquated river-fleet units with modern craft.

The port of Santarem, situated at the junction of the Amazon and the Rio Tapajos, has received a large sum to be used in constructing piers for deep-draft vessels. In northeest Brazil, a dam and hydroelectric plant were constructed at Barragem de Boa Esperanca on the Rio Parnaiba; locks at the site are to be completed in 1973. In eastern Brazil a \$55 million regularization project was begun in February 1972 on the Ric Sao Francisco; emphasis is on its middle 280-mile sector in the State of Minas Gerais. In southeast Brazil the Rio Tiete, Rio Taquari, and Rio Jacui are the targets of major improvements. Developments on the Rio Tiete, which is now being dredged, consist of a dam and navigation locks at Bariri and Barra Bonita, completed since 1970; a dam under construction at Promissao (plans for navigation locks are under study); and a dam at Ibitinga where work on navigation locks nears

completion. The Bariri locks opened 125 additional miles of navigation in this system. The Rio Taquari is being dredged to permit barges with 10-foot draft to navigate as far as Porto Mariante, a wheat and soya bean production center about 64 miles upstream from Porto Alegre; navigation locks are under construction at the Bom Retiro do Sul dam on the Rio Taquari. Two locked dams adjoining hydroelectric plants have been completed on the Rio Jacui, and a dam-lock installation has been projected for construction at Santo Amaio do Sul on the same stream. These three installations will increase Rio Jacui navigability to 150 miles upstream from Porto Alegre.

An east-west waterway for the State of Rio Grande do Sul, connecting the Rio Ibicui, tributary of the Uruguay, with the Rio Jacui by means of a 95-milelong canal, is in the final planning stage.

In southwest Brazil navigation locks are under construction at the hydroelectric plant dam near Jupia on the Rio Parana; when the dam and 4-million-kilowatt hydroelectric plant at Promissao, some 30 miles upstream from Jupia, are completed in 1973, navigation locks are to be installed, making the Rio Parana navigable in Brazil for almost 450 miles. Work being done on the Rio Parana and Rio Tiete are to create a navigable waterway of about 870 miles between Salto das Sete Quedas at Guaira on the Rio Parana and Sao Paulo on the Rio Tiete. Studies are in progress to develop the northwestern and northeastern rivers to coordinate traffic with the major highways connecting commercial and industrial centers with remote regions.

Characteristics of principal inland waterways are given in Figure 6.

# F. Pipelines (C)

The pipeline systems of Brazil are confined to the highly industrialized centers and the oil producing areas near the Atlantic seaboard. Control is exercised by the government through its petroleum monopoly, PETROBRAS, Petroleo Brasileiro—and the Sao Paulostate-owned Santos-Jundiai Railway Company. Since industrial growth has been a recent phenomenon, the petroleum facilities are relatively new and rapidly expanding.

About 65% of Brazilian crude oil requirement is imported; the remaining 35% is produced from domestic oilfields, primarily in the state of Bahia. Oil discoveries in the States of Sergipe and Maranhao, though encouraging, are expected to do little more than keep abreast of increasing domestic needs. Because of the great distances between the oilfields

			SAFE DRAFT	RAFT	
NAME	TYPE	NAVIGABLE LENGTH	Low	High	REMARKS
		Miles*	Feet	et	
Amazon Kiver	Natural stream	1,967	23	na	Navigable by coastal-type vessels throughout and by standard ocean-type vessels upstream about 1,100 miles to Manaus. With tributaries provides NW. Brazil with more than 20,000 miles of seasonally navigable waterways, empties into Atlantic Ocean through numerous delta channels. Important navigable tributaries: Rio Negro, Rio Madeira, Rio Purus, Rio Tocantins. Chief cargoes carried downstream: crude petroleum, petroleum products, rubber, timber, cattle, oil-hearing nuts, cotton, rice, cacao.
Rio Sao Francisco	Partially improved stream	1,005 (126–879)	က	ro.	Chief cargoes carried upstream: processed foodstuffs, building materials, oilfield equipment, manufactured goods.  Navigable between mouth, near Piacabucu, and mile 126, and between mile 348 at Santa Maria da Boa Vista and mile 1.227 at Pirapora. Navigation interrupted between mile 126 and 348 by impassable rapids and falls. Small steamers navigable from river
Lagos d 18 Patos-Rio Guaiba	Improved lake channels	166	13.5	16	mouth, co mue 126; river steamers and diesel-powered barges operate regularly between Juazeiro, mile 429, and Pirapora, mile 1,227, both RR. centers. Depth over bar at mouth 9 ft. at low water. River flows WNW. for about 350 miles from Atlantic Ocean, thence S. in irregular course. Cargo carried consists chiefly of mineral and agricultural products.  Most important and most developed waterway in Brazil. Navigable channel 1,800 ft. wide, 26 ft. deep at low water, leads from seu 10 miles to lake. Lake encumbered by numerous shoal areas to Porto Alegre on Rio Guaiba. Channel in Rio Guaiba dredged to 18 ft.
Rio Uruguai	Natural stream	694	Remarks -	: : : :	Joined by Rio Jacui just upstream from Porto Alegre. S. end of Lagon dos Patos connected with Lagoa Mirin by 43-mile-long Canal Sao Gonealo, which serves as outlet for Brazilian and Uruguayan hinterlands; canal navigation limited to river craft and steamers by normal controlling depths of 10 ft. in dredged channel at entrance to Lagoa Mirim. Cargoes carried; grain, fruit, sugar, other agricultural products, coal, hides, lumier, petroleum products, manufactured goods.  Serves Brazil prima-ily as transport route for rafting timber from upper reaches downstream and for local transport of agricultural products, salt, ranch suppilies, and other consumer goods. Borders Argentina for 445 miles in W. part of State of Rio Grande do Sul. Provides connections with Argentina and Uruguay. 445-mile section between Brazil and Argentina and Uruguay, 445-mile section between Brazil and Argentina and tugs with steel barges up to 72-ton capacity launches and tugs with steel barges up to 72-ton capacity launches and tugs with steel barges in mile 310 and mile 575, at Pre-to Xavier controlling doubt is 6 ft.

sate drait, 3 it.; in upper reaches, mile 3/3 to mile 1,004, Marcelino Ramos, in SE. Brazil (upper limit of navigation), safe draft is 2 to 3 ft., navigable mostly by rafts, tugs, launches. International RR. and highway bridge between Brazil and Argentina at Uruguaian, mile 362.  Remarks Provides transport route to 6 Brazilian states and trade route to Argentina, Paraguay, Bolivia. Enters Brazil near Foz do Iguacu, mile 1,048, at Paraguay, Argentina frontier with Brazil. Forms 127-mile border with Paraguay, from mile 1,048 to mile 1,175 at Guaira, site of rapids and falls, Salto das Sete Quedas. Navigable by 300-ton-capacity river vessels between mile 1,048 and	mile 1,130 at Porto Mendes, flowing through deep gorge; normal controlling depth 36 ft., safe draft, 6 ft.  Not navigable for 45-mile stretch mile 1,130-mile 1,155, at Guaira.  Mile 1,175-mile 1,494, at Jupia, depths are 25 ft. at low water, but iew shallow passages fimit navigation to shallow-draft vessels.  Navigable by heavy towed barges from mile 1,494, site of Jupia hydroelectric plant dam (navigation locks under construction), to mile 1,525, site of Ilha Solteira, larger hydroelectric plant dam under construction. Cataracts, Cachoeira Urubupunga, at mile 1,500, were eliminated by rise in water level produced by Jupia dam.	Typical log ratic used on Alto Pa, ana have draft of about 3 ft.  International highway bridge at Poz do Iguacu, RR. bridge at Jupia; highway bridge planned to span Rio Parana near mile 1.38f. 6 miles below Presidente Epitacio.  Cargo consists chiefly of lumber, logs, yerba mate, construction materials, general consumer product.  Remarks Important to development of vast Mato Grosso area. Forms boundary between Brazil and Bolivia mile 770. mile 800 and between Brazil and Paraguay mile 572-mile 770. Navigable for 678 miles by launches and smali shallow-draft craft from mile 572 at Paraguay border to Caceres at mile 1,250; open to international	navigation from mile 924, at Corumba, southward. Steamers of 1,000-ton capacity navigate to Cuiaba via tributary. Rio Cuiaba, at high-water stages; barges used during low-water period. Vessels of 2,000-ton capacity navigate to Corumoa, mile 924, except at low water when safe draft is about 4.5 ft. Corumba mile 1,046, safe draft usually 3 to 3.5 ft.; low water, Nov. Feb., ab., e. corumba. RR. bridge spans river at Porto Esperanca, mile 845. Corumba is most important commercial port in upper Rio Paraguay basin. Eventual connection of Rio Paraguay head-waters with Rio Guapore, navigable tributary of Amazon River, envisioned in national transportation plans. Chief cargoes carried downstream: manganese ore, dried beef, hides, sugar cane, rubber, agricultural produce. Chief cargoes carried upstream: sugar, salt, petroleum products, staple food items, general merchandise.
432 (82 + 319 ÷ 41)		678	
Rio Paranadodo		Rio Paraguay	

na Data not available. \*Lengths are for Brazilian sections of the rivers.

and the processing centers, there is double handling of crude by pipelines and tankers.

Crude-oil pipelines are utilized for transporting crude oil from domestic fields to export marine terminals and from import marine terminals to refineries in industrialized areas. The products pipelines are used for transport of imported and locally refined products. There are 1,087 miles of pipelines in operation; 773 miles are used for crude oil, 290 miles for refined products, and 24 miles for natural gas.

In the State of Bahia 144 miles of crude-oil and 24 miles of natural-gas pipelines connect the oilfields with each other and with the marine terminal at Madre de Deus and the Mataripe refinery. Production in the Bahia area is about 140,000 barrels a day. The refinery has a crude-distillation capacity of 45,000 barrels, leaving 95,000 barrels a day for shipment to other parts of the country.

The first pipeline and marine oil terminal in the State of Sergipe was inaugurated in December 1966. This 30-mile pipeline taps the Carmopolis oilfield (about 18 miles north of the port of Aracaju) and adds a minimum of 16,000 barrels a day to Brazil's crude-oil production. Long-term expansion to 100,000 barrels a day is planned for the area.

The state of 'sao Paulo, Brazil's largest industrialized area, imports all of its petroleum products through marine terminals at Santos and Sao Sebastiao. Crude oil is delivered to four refineries by 277 miles of pipeline; refined products are distributed by an additional 187 miles of pipeline.

The longest single pipeline in Brazil covers a distance of 227 miles between Rio de Janeiro and Belo Horizonte. This line, which formerly transported refined products from the Duque de Caxias refinery in Rio de Janeiro, has been converted to transport crude oil from the Rio de Janeiro marine terminal to the new Gabriel Passos refinery in Dalo Horizonte. A 91-mile pipeline carries fuel oil to the important industrial area of Volta Redonda and to the marine terminal of Santa Cruz. An additional 48 miles of crude-oil and products pipelines also connect the refinery in Rio de Janeiro with local port facilities and POL storage terminale.

The only gas pipelines in the country are those in the state of Bahia, where the gas is probably being injected into the Candeias oilfield to increase oil production.

Details of principal pipelines are given in Figure 7.

# G. Ports (C)

Brazil has six major ports and 25 significant minor ports. Rio de Janeiro and Santos (Figure 8), both on the southeastern Atlantic coast, are the principal

maritime centers. The other four major ports are Recile, Salvador, Porto Alegre, and Rio Grande. Four of the significant minor ports, Belem, Sao Luis, Fortaleza, and Areia Branca, are on the less populated north coast. Manaus, almost 1,100 miles upstream from the mouth of the Amazon River, is the trading center for a vast hinterland and exports rubber and other agricultural products and receives general cargo for distribution through a flourishing international free zone. On the more densely populated east coast are the following significant minor ports:

Natal	Ilheus	Para
Cabedelo	Tubarao	Itaja
Maceio	Vitoria	Flo
Aracaju	Angra dos Reis	Tra
Aratu	Sao Sebastiao	

Paranagua Itajai Florianapolis T*r*amandai

Characteristics of the minor ports are consistent with the type of commodity produced and the imports needed in the respective areas. Belem, the most important commercial port on the north coast and headquarters of the Fourth Naval District, exports rubber, cacao, timber, and hides. Belem yards have two large floating drydocks and four marine railways and perform major hull and routine machinery repairs to naval and merchant ships. Most of the port activities at Fortaleza have been transferred recently to nearby Mucuripe from which cotton, ores, and salt are shipped. Areia Branca is being converted into a salt-distribution port because of its proximity to large salt flats. Natal ships salt, cotton, sugar, and ore; the floating drydock at the naval base repairs ships up to 2,000 tons. Cabedelo's principal shipments are sisal, sugar, and cotton. At Maceio a sugar terminal under construction has alongside depths suitable for large oceangoing vessels. Aracaju is undergoing dredging and extension of berthing space. Aratu, about 15 miles north of the major port of Salvador, is the site of new industrial plants and a naval base, which has the second largest drydock in Brazil. Ilheas is Brazil's leading cacao export port. The new port of Tubarao, owned and operated by a large mining company and completed in 1966, is designed especially for the shipment of iron ore and the receipt of coal; in 1970 it shipped over 22 million tons of iron ore, and the expansion of port facilities continues with the construction of an additional ore berth at depths suitable for vessels of 400,000 d.w.t. Vitoria has become a general-cargo and grain-handling port since most of its ore handling operations have been transferred to Tubarao. Angra dos Reis, about 75 miles south of Rio de Janeiro and site of the large Verolme shipvard, ships coffee, bananas, and rum and receives wheat, coal, and salt. The petroleum terminal built by

C	
) pelines	
Principal	
7.	
GUR	

From					
	То	LENGTH	DIAMETER	PRODUCTS TRANSPORTED	REMARKS
Bahia (state):		Miles	Inches		
Agua Grande oilfield	Madre de Deus	*37	12	Crude	Transports crude to Mades de Dame
Do		30	6.59	do	78,000 bbl./day capacity: I pumping station.
Buracica	Candeias.	37 25	12 8-12	do	Connects Burnains and amounts. efter 11
	Madre de Deus	<b>;</b> *	18	op	
Do	Matazipe refinery.	# m	6 5g 8 7g	do	Thanshorts and from Canal
Dom Joao	Candeias	9	65,8	do	has capacity of 45,000 bbl/day.  Connects Dom Joan and 9 sets 11 capacity of 50.
MirangaSergipe (state):	Aqua Grande	14	œ	do	terminal.  Completed 1965; has I numning station.
Carmopolis	Atalaia Velha	30	81	do	50,000 bbl./day capacity: future exnansion to 75 000 n.s.s et
Sao Paulo (state): Ilha do Barnabe	See Death and				100,000 bbl./day.
	Sao radio femnery	<del>1</del> 3	1,23/1	do	Transports crude from port of Santos via 2 minima statical
Sao Bernardo do Campo	Capuava refinery	7	123/4	do	to Sao Paulo area.  Branch line of 11ha do Brancha Co. D 1:
Sao Sebastiao	Cubateo refinery	75 140	22	do	km. from Santos.  Transports crude to Cubatao refinery; has 2 pump stations.  Transports crude to Daniels.
Paulinia	Barueri	09	10-14	Refined	capacity, cause to raumina remery; has 100,000 bbl./day capacity.  2 parallel lines scheduled for completion in 1072
		2	Ĉį	Crude	Transports crude from marine terminal in port of Santos to
Do	Sao Caetano pumping station	35	<u>*</u>	Refined	reinery; has 1 pumping station. Serviced by 3 pumping stations
	Cubatao refinery.	35	109/	do	2 parallel lines serviced by 2 pumping stations.
Do	do	2 01	<u>*</u> ∞	do	
Capuava refinery	do	6 1	6,5,8	do	
	Cubatao refinery	12	္က မာၻ	do	
:	oao rauio (riratininga thermal powerplant).	9	18		Branch line of 18-inch Alamoa-Utinga line from a point 41
Footnote at end of table					km. from Santos.

PETROBRAS at Sao Sebastiao accommodates 150,000-ton tankers, and expansion is nearing completion to handle 300,000-ton supertankers; the port supplies crude petroleum to three large refineries in the State of Sao Paulo. Paranagua ranks just below Santos in the shipment of coffee and receives large quantities of wheat, petroleum, and cement; a container terminal is under construction. Italai is a commercial center for industrial interests in and; its principal exports are tobacco, rice, timber, and marble. Florianapolis, headquarters of the Fifth Naval District, is decreasing in in portance as a commercial seaport. Tramandai, a new persoleum terminal owned and operated by PETROBBAS is capable of mooring 200,000-ton tankers bringing crude oil to refineries located inland.

Maritime ports are vital to the Brazilian economy because of the marked concentration of agricultural, mining, and industrial activities in or near the coastal areas. Coastwise shipping accounts for a large volume of maritime traffic. Crude petroleum, petroleum products, and wheat composed the bulk of coastwise cargo handled in the period 1962 through 1970. Coastwise traffic, concerned principally with the export of coffee, iron ore, sugar, cacao, and cotton and the import of crude petroleum and petroleum products, machinery, wheat, fertilizers, chemicals, and pharmaceutical products, more than tripled in 1970.

Movement of cargo through Brazilian ports increased about 6% in 1969 and 12% more in 1970. The greatest increases were in the ports of Vitoria, Tubarao, Maceio, Recife, and Paranagua.

A national program of port expansion and modernization, in progress since 1964, calls for constructing new piers and wharves, dredging channels and harbors, acquiring cargo-handling equipment and harbor craft, and constructing warehouse and containerization facilities. Almost all Brazilian vorts have benefitted from this program.

Brazil has 10 principal shipyards and numerous boatyards. Six of the principal yards, including the Japanese-Brazilian yard, Ishikawajima (Ishibras), are in the Rio de juneiro area. Under construction by Ishibras and scheduled for completion in 1973 is a new drydock capable of holding ships up to 400,000 tons. The principal naval base at Rio de Janeiro has extensive shipbuilding and ship-repair facilities. The Dutch-Brazilian yard, Verglme do Brasil, which has two shipbuilding docks, is located at the port of Angra dos Reis; in 1971 it delivered a 53,500-d.w.t. bulk-cargo carrier, the largest ship ever built in South America. One of the largest drydocks in Brazil is at the naval base in Aratu.

Brazilian ports are administered by the National Department of Ports and Navigable Routes (DNPVN) under the Ministry of Transportation and Public Works; authority, however, is delegated in various ways. The port of Rio de Janeiro is administered by the federal government through a special port agency; 11 ports, including Recife, Porto Alegre, and Rio Grande, are administered by state concessions; three ports, including Salvador and Santos, are administered by private "dock company" concessions; five ports, including Manaus, are under direct control of the DNPVN; two, Aracaju and Maceio, are under a combination of the DNPVN and the respective state governments; and two, Fortaleza and Belem, are under "mixed economy societies." Special petroleum, iron-ore, coal, and fertilizer terminals are administered by owner companies. A large dredging company (Companhia Brasileira de Dragagem) owned and operated by the DNPVN renders service to numerous ports, as required. Administration of the various ports is subject to change as new needs arise.

Ports are being improved in direct ratio to the accelerated industrial and commercial growth of the country and as a result of recent studies showing that some facilities were unable to handle international and domestic trade adequately.

Details of the major ports are given in Figure 9.

#### H. Merchant marine (C)

Few countries depend so heavily on waterborne shipping, both foreign and domestic, as does Brazil. A long coastline, a concentration of population and economic activity along the scaboard area, and inadequately developed land transport have stimulated development of a necessary, extensive, and increasingly efficient maritime system.

Most coastal shipping is handled by Brazilian-flag ships operating in liner (scheduled) service. In 1960 the cargo in this traffic amounted to 7.86 million metric tons; by 1970 the volume had increased to 14.29 million metric tons. The rise was due to a great increase in coastwise carriage of oil and ore, which more than offset a drop in the volume of general carge carried. Coastal service continues to be vital to the five northern States of Para, Maranhao, Piaui, Ceara, and Rio Grande do Norte and important to the central region and to Rio Grande do Sul in the south. However, it is doubtful that the former volume of general trade, which had been lost through inefficiency and erratic sailing schedules, can ever be completely regained. The two main streams of coastal



Rio de Janeiro, including naval base at upper right

FIGURE 8. Rio de Janeiro and Santos, major ports (U/OU)

traffic are from the southern states to the central region and from the north and northeast states to the central region.

Brazalian foreign trade, which is preponderantly scaborne, amounted in 1971 to a total value of about US\$2,900 billion in exports (principally coffee, cocoa, sugar, iron ore, cotion, and manufactures) and US\$3,250 billion in import. (principally petroleum, wheat machinery, and chemicalia). Major trading

partners are the United States, West Germany, the United Kingdom, Italy, the Netherlands, Argentina, and Venezuela. In 1970, Brazilian-flag ships carried 10.4%, by volume, of Brazil's exports and 20.6%, by volume, of her imports. Brazilian companies, operating with chartered foreign-flag ships as well as their own vessels, accounted for 21.7% of the volume of Brazilian exports and 56.5% of the volume of her imports. Freight charges on these cargoes returned



Santos

U\$\$254 million to Brazil and surpassed coffee exports and the mining of iron ore as a national source of income, according to an announcement by the Minister of Transportation and Public Works. However, the continuing need to charter foreign tonnage to supplement Brazilian ships in their worldwide service was also cited as contributing as much as 50% to the annual deficit in the "services" sector of the balance of payments. During 1970, the state-

owned shipping entity, Lloyd Brasileiro, operated in international traffic with 30 of its own ships and 20 chartered foreign-flag vessels. During 1969, 11 Brazilian companies operating in foreign trade chartered 357 foreign-flag ships for that trade, the charter fees amounting to US\$118.1 million. Since 1969, the percentage of the total fleet deadweight tonnage involved in foreign trade has increased from about 50% to over 75%.

ί	J
1	2
Maior	
0	:
100	

NAME; LOCATION;

Natural, well-protected, coastal, in Baia de Guanabara, one of finest natural harbors in E. part, 15 sq. miles; Governador in NW. part, 20 sq. miles; Rio, in SW. part, in world; divided into 3 sections; Niteroi, Largest and most complex port; cultural, commercial, and Receipts-grain, coal, crude and refined petroleum industrial center. Cargo handled at record high in 1970. iron and manganese ores, other minerals, coffee, cocoa, products, salt, fruit, manufactured goods. Shipments-ESTIWATED MILITARY PORT CAPACITY\* 22°54'S., 43°14'W Rio de Janeiro...

Principal shipbuilding and ship repair center; 8 graving docks, largest 760 x 131 ft.; 2 hipbuilding docks, largest 1,148 x 213 x 28 ft.; 2 floating drydocks, largest 626 x 85 ft., lifting capacity 11,000 tons; 2 marine railways, largest hauling capacity 55 tons. cotton, canned meats, hides.

depths in berths.

Frincipal port of Sao Paulo, most highly industrialized Principal naval center. Hq. of Brazilian Navy and 1st state and rich coffee-growing area; leading coffee export port of world. Movement and handling of cargo Naval Dist .; extensive operational, logistical, training facilities with supporting activities, important shipyard. continually increasing. Has container-handling area. Construction and improvement of port facilities on left bank of estuary under way. Receipts grain, chemicals, coal, fertilizers, machinery, crude and refined petroleum products. Shipments-coffee, sugar, bananas, citrus fruits, hides, textiles.

23°57'S., 46°20'W.

30,000

Limited hull, boiler, engine repairs; 4 marine railways, largest 412 ft. long, hauling capacity 600 tons.

Minor naval communications facility and school. Chief port and principal administrative, commercial, industrial, transportation center of State of Rio Grande do Sul; chief industrial activity processing important inland waterways and largest in volume of agricultural products; major center of transshipment in Lagoa dos Patos system, one of Brazil's most cargo handled.

Receipts-wheat, fruits, machinery, timber, sugar, meat, coal, coke, fertilizers, iron and steel, salt, refined petroleum products. Shipments-lumber, wheat, meat and meat products, rice, tobacco, iron and steel

railways, largest hauling capacity 600 tons; 3 building Minor repairs and small-boat construction; 2 marine ways, largest 490 ft. x 177 ft. 0

Alongside--For 12 large, 19 standard, 15 20 small coaster-type cargo vessels; 46 lighters; I standard ocean-, 10 standard coaster-type tankers; 2 large ocean-type tankers (offshore pipelines); 3 small small ocean-type cargo vessels; 9 standard, aircraft carriers; numerous berths for to 42 ft.; depths leading to berths exceed 15 sq. miles, principal cargo transfer area depths about 50 ft.; alongside depths, 23 and site of 2 largest shippards. General

other types of naval vessels. Fixed mooring-For 5 large ocean-type Anchorage-Large numbers of all classes. cargo vessels.

ocean-type cargo vessels; 7 small coaster-type vessels; 6 lighters; 2 large, 4 standard, 1 small ocean-type and 1 Alongside---7 large, 29 standard, 3 small standard coaster-type tankers.

Natural, coastal, in Santos estuary; area

about 21'2 sq. miles; general depths 20 to

42 ft., excellent protection; depths leading to berths exceed depths in berths.

cargo vessels, 44 lighters. about  $2l/_2$  sq. miles; excellent protection; channel has controlling depth of  $15l/_2$  ft.

Natural, river harbor on Rio Guaiba; area Alongside--For about 90 small coaster-type

26

Improved, natural coastal; area about 1 sq. breakwaters, reef; controlling depth 23 mile; afforded good protection i.y island, ft. (33 ft. MHWN) at entrance. Chief port and principal commercial, industrial, transportation center of region; closest deepwater Brazilian port to Africa and Europe, on sealanes connecting main South Atlantic ports of South America with North refined petroleum products, cement, hardware, chemical products, coal. Shipments—sugar, cotton, coffee, hides and skins, vegetable oil, alcohol, leather, timber. nually increasing; new construction of facilities and purchase of new handling equipment. Receipts-grain, America, Europe, North Africa. Cargo handled an-8°03'S., 34°54'W.

Recife.... 12,000 dinor hull and machinery repairs; 2 marine railways, Hq. of 3rd Naval Dist., secondary naval base with landlargest hauling capacity 1,500 tons.

Deepwater terminal for Lagoa dos Patos waterway sys-Rio Grande do Sul (state); other industrial activities include meat packing, fish and vegetable canning, brewtem; petr deum refining and distributing center for ing, textiles, cigarettes, footwear, animal products, ing, shipyard, ordnance, supply, communications petroleum, salt, wheat, chemicals, iron and steel products, coal, cement paper. Shipments-wheat, frozen meats, agricultura training, medical, miscellaneous facilities. pharmaceuticals. Receipts-crude

32°02'S., 52°05'W.

Rio Grande....

Minor hull and machinery repairs: 2 marine railways, each has hauling capacity of 1,200 tons. products, rice, wool.

12°59'S., 38°31'W.

Salvador

Capital and principal commercial center of Bahia (state); port serves primarily as exporting port for agricultural and mining hinterland. Port expansion and developcoal, grain, refined petroleum products, iron and steel ment program under way. Receipts-general cargo, cacao, manganese and iron ores, wax, coffee, sugar products, machinery, paper products. Shipmentshides, tobacco, grain, hemp.

Limited floating and engine repairs to naval and commercial small ships. 4q., 2nd Naval Dist. and secondary naval base; components include ship repair, supply, training, medical miscellaneous facilities.

Alongside--For 5 large, 8 standard, 4 small ocean-type cargo vessels; 2 small coastertype vessels; 9 lighters (5 standard oceantype tankers, alternative berths).

Anchorage .- Large numbers of all classes, 1 Fixed mooring—For several standard oceanto 5 miles SE. of harbor entrance. type cargo vessels.

Alongside-For 11 standard ocean-type cargo vessels; 1 standard, 9 small coastertype cargo vesseln; 1 lighter; 1 small oceantype, 1 standard coaster-type tankers. Ir.proved, natural harbor, well protected, at N. end of channel connecting Atlantic Ocean with Lagoa dos Patos; area

Anchorage-Large numbers of all classes in Alongside-For 3 large, 5 standard oceanroadstead outside harbor 1 sq. mile; 2 parts—Porto Novo, depths 19 to 29 ft., Porto Velho, depths 11 to 18 ft. Dredged channel extends length of Porto Novo, least depth 26 ft.; connect-Improved natural, coastal harbor; area about 500 acres; 2 breakwaters afford only rair protection; general depths 7 to

ing channel has depth of 33 ft.

type cargo vessels; I small chaster-type cargo vessel; 6 lighters; 1 standard ocean-Anchorage—Large numbers of all classes outside breakwaters in Baia de Todos os type tanker.

34 ft.; depths leading to berths exceed

depths in berths

\*The estimated military port capacity is the maximum amount of general cargo-expressed in long tons-unat can be unloaded onto the wharves and cleared from the wharf aprons during a period of one 24-hour-day (20 effective cargo-working hours). The estimate is based on the static cargo-transfer facilities of the port existing at the time the estimate is pre-pared and is designed for comparison rather than for operational purposes; it cannot be projected beyond a single day by straight multiplication. In July 1972, the Brazilian merchant fleet consisted of 213 ships of 1,000 gross register tons (g.r.t.) and over, totaling 1,609,602 g.r.t. or 2,363,393 deadweight tons (d.w.t.), as follows:

TYPE	No.	G.R.T.	D.W.T.
Dry cargo	133	694,292	929,088
Tanker	42	542,177	881,696
Naval tanker*	3	8,867	13,855
Bulk cargo	18	183,273	285,916
Combination tanker/ore		•	·
саттіег	2	121,220	210,839
Refrigerator	6	21,288	21,985
Liquefied-gas carrier	5	15,277	11,444
Passenger	2	20,894	6,970
Combination passenger/			-
cargo	2	2,314	1,600
	213	1,609,602	2,363,393

<sup>\*</sup>Known to be used commercially.

Among the merchant fleets of South America, the Brazilian fleet is both the largest and the most modern. The largest ship in the fleet is a 116,195-d.w.t. tanker (Figure 10). Additional characteristics are given in the following tabulation:

	I ERCENT OF
	D.W.T.
Are (years):	
Under 10	65
10 to 19	23
20 and over	12
	No. of ships
Size $(d.w.t.)$ :	
Under 10,000	133
10,000-19,999	63
20,000-99,999	13
Over 100,000	4
Service speed (knots):	
18 and over	<b>30</b>
14.1 to 17.9	63
Under 14	
Power/fuel:	
Diesel	168
Steam/oil	44
Steam/coal	1

Fleet ownership is divided among 44 government and private beneficial owners (entities assuming profit or loss from operations). The largest of these is the Government of Brazil, which owns and operates 91 ships under five semiautonomous entities known as autarquias. Aside from the government, only eight owners have more than four ships. These owners and the government operate 92% of the total fleet deadweight tonnage, and the remaining 8% is distributed among 35 owners. Four private owners and two government autarquias each operate more than 100,000 d.w.t. of shipping. The largest of these,

PETROBRAS, provides 96% of the fleet's total tanker deadweight tonnage through its operating arm, Frota Nacional de Petroleiros—FRONAPE which owns and operates 858,258 d.w.t. Two small Brazilian-flag tankers, each under 1,500 d.w.t. are foreign owned, one by the Shell-Royal Dutch Group of London and the other by Standard Oil of New Jersey. Two ships are registered under the Liberian flag.

In January 1971, in addition to merchant ships of 1,000 g.r.t. and over, there were about 90 merchant ships between 160 g.r.t. and 999 g.r.t., totaling 36,000 g.r.t. Of these, about 80 are dry-cargo ships, most operating in the coastal and river trade. In 1971, Brazil's fishing fleet consisted of more than 300 vessels, including about 25 occuragiong ships between 100 and 400 g.r.t. and totaling about 5,000 g.r.t.

The Brazilian merchant marine program has long supported the modernization and expansion of a chronically aged and inefficient merchant fleet. This program, pursued sporadically since long before World War II, was stepped up at the war's end with the acquisition by the government of 20 oceangoing freighters and 12 CI-M-AVI type U.S.built coastal freighters. It was further implemented in 1956 with the addition of 12 more of the same type coastal vessels. In the intervening period, PETRO-BRAS and FRONAPE began operations with a fleet of about 20 tankers and four river vessels. However, the combined efforts of government and private capital were not sufficient to sustain the growth of the fleet through new acquisition or to renovate the many older units then in operation. In response to a critical need for financing, and in order to diminish the outward flow of foreign exchange due to Brazilian cargo being carried in foreign ships, a fund and tax plan was promulgated in 1958.

The fund for merchant fleet renovation and expansion was tied closely to a strong plan for improving the domestic shipbuilding and repair industry. Government loans administered through the Merchant Marine Commission (CMM) from the Merchant Marine Fund (FMM) and for up to 85% of a ship's price are made available to offset the difference in construction cost between Brazilian and foreign vards. The FMM has been made partially selfsustaining by imposition of the Renovation Tax for the Merchant Marine, also promulgated in 1958 as a part of the FMM. This tax consists of a charge of 20% against cargo owners on freight receipts generated both in international and coastwise trade. Money from the tax is deposited with the National Bank of Brazil and is earmarked for parchasing, building, and modernizing ships.



FIGURE 10. The Horta Barbosa (62,619 g.r.t., 114,800 d.w.t.), shown here, and the Hamilton Lopes (62,619 g.r.t., 116,195 d.w.t.), government-owned tankers, are the largest ships in the Brazilian merchant fleet. Both ships were acquired in 1969. (U/OU)

At the outset of the program, before it could get underway domestically, orders were placed abroad for new ship construction and used tonnage was acquired to replace the oldest vessels. The bulk of these orders were planned to extend from 1958 through about 1961, when the domestic shipbuilding industry was scheduled to begin phasing into large-scale production for the Brazilian merchant fleet. Tankers were purchased mainly from Dutch, Japanese, and Danish yards, and most new freighters came from Polish and Finnish yards. New tonnage in dry-cargo and combination passenger/cargo ships was virtually offset by scrapping old tonnage, but tanker tonnage increased by 30%.

Between 1960 and 1968 the government program resulted in the construction for Brazilian owners of 61 ships of 527,000 d.w.t. in Brazilian shipyards. The program was reaffirmed and accelerated in 1967-68, and by September 1969 an additional 65 ships of 1,275,000 d.w.t. were on order from Brazilian yards for Brazilian owners. By January 1972, 90 Brazilian-built ships aggreg sting 782,787 d.w.t. and representing 35% of the total fleet deadweight tonnage were in service under the Brazilian flag. Domestic construction has produced 61% of the dry cargo deadweight tonnage.

As of 30 April 1972, 68 ships aggregating 2,626,890 d.w.t. were on order for the domestic fleet. This included 40 dry cargo, 11 tankers, eight bulk carriers, and nine combination tanker/ore carriers. The largest ships on order were five 131,000-d.w.t. and one 265,300-d.w.t. combination tanker/ore carriers.

There is no inclusive body of law encompassing the maritime sector in Brazil. Authority is based on executive decree and regulation except when based on, or flowing directly from, specific articles of the

constitution. In general, the government's policy has been to encourage the growth of the merchant fleet so as to enable it to carry at least half of Brazil's foreign trade and all of the coastwise trade.

The specific goal of government policy is the reservation of the majority of trade between Brazil and each of her trading partners individually to the ships of the countries involved through bilateral negotiation and agreement. Under such agreements, 40% of the trade would be carried by Brazilian ships and 40% by those of the trading partner. The remaining 20% would be available to third country ships. The amount of Brazilian trade carried by Brazilian ships has steadily increased as a result of this policy and of the government's direct supervision of shipping conference arrangements. The increased proportion of domestic cargos carried also is a result of the use of more modern ships in the Brazilian fleet and the allocation of overseas lines to Brazilian companies previously restricted to coastal operations, diverting Brazilian tonnage to that trade. Some shipping lines of countries not party to the bilateral arrangements, especially those of Scandinavian flags, have withdrawn their ships from the Brazil-North American trade due to the steadily decreasing amount of that trade carried by them.

Government policy with regard to cabotage, or coastal trade, restricts such operations to the nation's own ships or to those chartered by Brazilian companies when Brazilian ships are not available. A principal policy objective has been to reestablish confidence in this means of transport, which has long suffered from lack of dependable service. Lines serving the coastal trade are now required to maintain regular schedules of service. All ships in this trade, including foreign

charters, are under explicit governmental regulation and regardless of flag are controlled as if they were Brazilian owned.

In chartering fore,gn-flag ships for both coastwise and high-seas services. Brazilian lines utilize ships only with the case-by-case approval of the government and may only charter deadweight tonnage up to the level of new tonnage on order for their own account. Chartered tonnage, as well as Brazilian-flag tonnage, is taxed at the rate of 20% of the freight payment, the money going to the fund for merchant marine renovation. This money is returned to the owners in proportion to tonnage under construction to their order.

The government extends direct aid to Brazilian shipping in several forms. Operating deficits of government-owned ships are absorbed, both for cabotage and international operations. Newconstruction loans are made for up to 85% of construction cost and are to be repaid out of revenue at 6% interest over 15 years. Indirect aid to the merchant marine is extended through selectively granting duty-free imports, giving preferential treatment in carrying certain exports and imports, and by participating in the ownership and operation of merchant ships.

Brazil is party to the following international conventions or acts: The Inter-Governmental Maritime Consultative Organization (IMCO); International Convention for the Safety of Life at Sea, 1960; International Regulations for the Prevention of Collisions at Sea, 1960; and International Convention on Load Lines, 1966. Maritime Affairs are administered by the National Merchant Marine Superintendency (SUNAMAM) under the Ministry of Transportation and Public Works, which in 1969 succeeded the Merchant Marine Commission. SUNAMAM consists of five departments (Engineering, Finance and Control, Plans and Studies, Navigation, and Administration). It has regional agencies within Brazil and in Hamburg and New York.

SUNAMAM executes national maritime policy and participates in its formulation; regulates Brazil's overseas and domestic maritime trade; assigns routes to Brazilian companies; administers public resource as applied to merchant fleet renovation and subsidies; fixes certain tariff limits; negotiates working conditions and wages of stevadores and other port workers; participates in international conventions and effects their implementation by Brazil; authorizes the charter of foreign ships by Brazilian companies; regulates the administration of national shipbuilding

programs and the allocation of contracts for new construction; and authorizes expenditures on the merchant fleet outside Brazil.

All water transportation undertaken for Brazilian account or under the Brazilian flag, whether by governmental agencies or by private concerns, is regulated by the decrees of SUNAMAM. The Superintendent of the Merchant Marine is appointed directly by the President of the Republic.

On 1 January 1971, 6,367 seafaring personnel were employed on Brazilian merchant ships of 1,000 g.r.t. and over, 7% less than those employed afloat at the beginning of 1970. The decrease reflects both a desire to reduce manning levels and the greater use of automation in the more modern fleet. No official government steps have been taken toward preserving jobs threatened by automation.

Maritime labor, both afloat and ashore, is unionized under the National Confederation of Maritime, River, and Air Transport Workers. Much of this union's militant and politically active leadership was removed after the 1964 Revolution. The union is now rigidly controlled by and subject to the political vigilance of Brazilian naval authorities. Strikes are outlawed by the government.

Merchant marine training is accomplished through the Merchant Marine Academy at Rio de Janeiro, which is under the administration of the Brazilian Navy. The academy accommodates about 600 students and provides undergraduate and postgraduate instruction in deck, engineering, and steward departments. All graduates of the Academy are commissioned in the Naval Reserve.

#### I. Civil air (C)

Civi' aviation has a vital role to play in the present and future development of the Brazilian economy. International air services greatly strengthen the nation's ties with many of the major centers of the Western world. In addition, domestic air services are especially important in the undeveloped northern and central areas of the country where many settlements are separated by hundreds of miles and where surface transportation is inadequate or completely lacking. However, in spite of its importance, domestic air traffic has not increased as expected. A fleet modernization plan has helped, but additional planning and development are needed to provide a strong and reliable domestic air network. A major problem which must be solved is that of too many airlines serving the same points.

Sixteen foreign airlines serve Brazil; these together with the Brazilian airlines provide regularly scheduled services between Brazil and 39 cities in 31 countries. Brazil's Empresa de Viacao Aereo Rio-Grandense, S.A.—VARIG and Aerolineas Argentinas of Argentina are the only Latin American airlines providing a direct link between southern Africa and South America.

Brazil, which has over 3,700 registered aircraft, has one of the largest civil airfleets in the world. However, in the last few years the number of major (20,000 pounds gross weight or over) civil-transport aircraft has declined because of permanent grounding, storage, or sale of obsolescent aircraft and bankruptey encountered by some small companies. The following 110 civil aircraft of at least 20,000 pounds gross weight are registered and operating in Brazil:

4	Aerospatiale	Caravelle
	~~	

- 2 BAC 111-400
- 4 BAC 111-500 4 BAC Viscount 827
- 11 Boeing 707-320C 2 Boeing 707-420
- 8 Boeing 727-100 3 Boeing 727-200
- 6 Beeing 737-200
- 15 Douglas DC-3
- 4 Dou las DC-6C 1 Douglas DC-8
- 2 Fairchild C-82A
- 4 Fairchild-Hiller FH-227B 6 Handley Page Herald
- 10 Hawker Siddeley HS-748 10 Lockheed L-188 Electra
- 14 NAMC YS-11A

An estimated 36,000 persons are engaged in civil aviation activities, including about 3,250 commercial pilots and 16,700 private pilots. About 900 pilots are rated in heavy multiengine aircraft. Skilled maintenance personnel number about 6,500.

Three of the four major scheduled airlines in Brazil are privately owned. In addition there are about 70 air taxi and charter operators. VARIG, Brazil's chosen instrument for long-distance international flights and the largest airline company in Latin America, serves 59 domestic points and links Brazil with 22 cities in 20 countries. VARIG's routes extend two-thirds of the way around the world; a gap between Rome and Tokyo prevents VARIG from becoming a round-theworld airline. The company employs nearly 11,000 persons, including about 2,200 skilled maintenance personnel and 500 pilots. VARIG is a private enterprise, 70% owned by its employees. Its fleet consists of nine Boeing 707-320C's, two Boeing 707-420's, four Boeing 727-100's, one Douglas DC-8, 10 Hawker Siddeley HS-748's, and 10 Lockheed L-188 Electras.

Brazil's second major carrier, Servicos Aereos Cruzeiro do Sul S.A.—CRUZEIRO, serves 35 domestic points and six regional cities. About 85% of the company's stock is held by its employees. CRUZEIRO employs about 4,400 persons, including 185 pilots and 1,800 skilled maintenance personnel. Its fleet consists

of four Aerospatia! Caravelle 6R's, four Boeing 727-100's, eight Douglas DC-3's, two Fairchild C-82's, and eight NAMC YS-11A's.

SADIA S.A. Transportes Aereos—TRANSBRAZIL S.A. Linhas Aereas, a subsidiary of the privately owned Sadia Corporation, serves 19 domestic points and employs about 1,000 persons, including at least 35 pilots. Its fleet consists of four BAC 111-500's and six Handley Page Hearlds.

Viacao Aerea Sao Paulo, S.A.—VASP is the only major Brazilian air carrier that is not privately owned; over 90% of the company is owned by the State of Sao Paulo. VASP employs about 4,200 persons, including 170 pilots and 2,000 skilled maintenance personnel, and has an operating fleet consisting of two BAC 111-400's, four BAC Viscount 827's, six Boeing 737-200's, seven Douglas DC-3's, four Douglas DC-6's, six YAMC YS-11A's, and three Boeing 727-200's.

VARIG, CRUZEIRO, and VASP have joined a pool to provide high-frequency scheduled services via the *Ponte Aerea* (Air Bridge) between Rio de Janeiro and Belo Horizonte, Rio de Janeiro and Sao Paulo, and Rio de Janeiro and Brasilia.

Brazil's largest air-taxi operator is *Lider S.A. Transportes Aereos*—Lider Taxi Aero, which operates one Lear Jet 24, eight Aero Commanders, three Beech Barons, and three Cessna Skylanes. It employs 130 persons, including 40 pilots. From headquarters at Belo Horizonte, Lider provides services over an extensive network throughout Minas Gerais, as well as to Rio de Janeiro, Sao Paulo, and Brasilia. The balance of air-taxi and charter services fly light single- and twin-engine aircraft from Brazil's major cities to outlying areas.

In addition to the services operated by the scheduled airlines and charter carriers, the Correio Aereo Nacional, the airmail and general carrier division for the Brazilian Air Force, transports mail throughout the interior, linking about 100 small communities and villages where regularly scheduled private air transport is unavailable. Passenger and cargo are carried on a space-available basis.

The Directorate of Civil Aviation, under the jurisdiction of the Ministry of Aeronautics, is responsible for the control and coordination of all civil aviation activities. The Ministry of Aeronautics is concerned with all aspects of civil and military aviation and subjects civil air operations to strong military influence. Also attached to the ministry is the Committee for Studies Concerning International Air Navigation, an intergovernmental agency dealing with international aviation policy matters. The Study Committee for Airline Authorizations advises the

Director General of Civil Aviation on problems relating to the regulation of aspects of the domestic activities of national operators and the concession of new domestic airline services.

A variety of training activities is conduct 1 in Brazil. The major facility for aeronautical sciences, technology, and research is the Aerospace Technical Center, which provides work in airframe and airport design and training in airline management and operations. An advanced flying school and training center at Porto Alegre is maintained by VARIG and provides flying and maintenance courses for VARIG personnel. An additional VARIG training facility at Santos Dumont airport in Rio de Janeiro houses simulators for training flight crews in its Boeing 707, Hawker Siddeley 748, and Lockheed Electra aircraft. CRUZEIRO operates a training school subsidized by the government. A number of Brazilian personnel have been trained overseas; VASP pilots, for example, have been trained in the BAC 111 aircraft by personnel of Allegheny Airlines.

Most of the civil aircraft are overhauled in Brazil. SADIA and VASP have maintenance bases at Sao Paulo; VARIG's is at Porto Alegre, and CRUZEIRO's is at Rio de Janeiro. VARIG is capable of overhauling most of its gircraft. The British-owned Rolls Royce maintenance facilities in Sao Paulo overhaul and repair engines for VASP and SADIA and for several foreign airlines. Companhia Electromecanica-CELMA overhauls piston and jet engines for the Brazilian Air Force, Brazilian commercial lines, and several foreign companies. The company is government controlled and is reportedly one of the most efficient in Latin America. Among the foreign overhaul facilities used by Brazilian airlines are the Frankfurt, West Germany, shops of Lufthansa, which provides VARIG with modifications on its Boeing 707's.

The Brazilian Government actively encourages development of civil aviation. Subsidies are granted to all the major air carriers and to at least 14 charter companies and air taxis operating in the interior. Subsidies are available for international routes, for interior "social-service" routes, for equipment, and for defraying increased operating costs not covered by charges or other government aid. Private flying is encouraged through an extensive system of government-subsidized-and-regulated aeroclubs. This support is considered essential for development of air transport as well as a means of establishing a semitrained reserve for the Air Force.

Brazil is a member of the International Civil Aviation Organization (ICAO) and is represented on the ICAO council. VARIG and CRUZEIRO are full members of the International Air Transport Association (IATA) and VASP is an associate member. Brazil has international agreements or arrangements covering the exchange of air service with at least 31 countries.

#### J. Airfields<sup>2</sup> (C)

The air facilities system of Brazil consists of 2,411 airfields, 375 sites, and 18 seaplane stations. Of these, 40 civil, 16 joint military/civil, and 14 military are significant. Most of the airfields are located within a 300-mile wide band along the east coast. In the interior the greatest concentration of fields is found in the States of Minas Gerais and Sao Paulo in the southeast and in the southern region near the Uruguay border. The Amazon Basin has relatively few airfields, but the number is considered sufficient for this underdeveloped area. Inaccessible terrain dictates that many fields be located along waterways. Continued expansion of the economy and d velopment of the interior will require more and longer paved runways and at least minimum support facilities.

Galeao Airfield at Rio de Janeiro and Vira nes at Campinas have concrete runways of 10,000 feet which can support sustained neavy bomber operations. Galeao is Brazil's most important airfield. Navigational and communications aids include instrument landing system (ILS), area surveillance radar (ASR), VHF omnidirectional range (VOR), and approach control towers. There are complete refueling, meteorology, repair, and cargo handling facilities. Vira Copos has VOR, nondirectional radio beacon (NDB), approach control tower, and complete field facilities. Augusto Severo, Brasilia, Campo Grande, Guararapes, Pinto Martins, and Val de Caes have paved runways of 7,000 to 9,000 feet and facilities to support jet fighter and medium to heavy bomber operations. Campo dos Afonsos, Congonhas, Cumbica, Gravatai, Ponta Pelada, Salgade Filho, and Santa Cruz could support continuous operation of USAF fighter aircraft in the 30,000- to 50,000-pound class and medium transports.

The 116 airfields having hard-surface runways are in fair to good condition. Weight bearing capacity, in general, is consistent with length of runway and significance of field. Some shorter runways are rated as strong as others of greater length. For example,

<sup>&</sup>lt;sup>2</sup>For detailed information on individual air facilities in Brazil, consult Volume 4, Airfields and Scaplane Stations of the World, published by the Defense Mapping Agency, Aerospace Center, for the Defense Intelligence Agency.

Congonhas, which has 5,700 feet of concrete, is rated at 800,000 pounds for aircraft with twin dual-tandem landing gear, as is Galeao, which has 10,827 feet. The more important fields have adequate to good taxiway and apron systems consistent with existing traffic and aircraft types. Smaller fields having paved runways have few or no taxiways and one or two small gravel or asphalt aprons. Cargo-handling equipment varies from crude to sophisticated according to need. Airline operations number from one or two flights per week from fields in outlying areas to 1,700 scheduled international and domestic departures from the Galeao/Santos Dumont complex at Rio de Janeiro.

The 2,295 temporary- and natural-surface runways are suitable for light-transport and liaison aircraft. Surfaces are gravel, clay and sand, graded earth, and grass, condition varying from poor to good depending on location, weather, and maintenance. Many fields lie along river lowlands and are not usable during the rainy season. Airstrips are built for the express purpose of road construction and continue to be used as towns are built along the roads. Practically all fazendas (ranches) have their private strips.

The larger seaplane stations are located near cities along the north and east coasts; operations consist of patrol and rescue work. Support facilities are adequate to good. Operating areas are just inside the mouths of large rivers or bays for sheltered anchorage. Inland seaplane stations with few facilities other than fuel and anchorage are located along the Amazon River and its major tributaries.

O

The 375 sites are former usable airfields; most have returned to natural state and have little or no potential without clearing and grading.

Maintenance is fair to good for major fields supporting military, international, and domestic air traffic. Marginal runway, taxiway, and apron weight capacity for the volume and type of traffic on many fields keep them in coastant need of repair. Minor fields of temporary or natural surface receive little or no maintenance. Support and service facilities are available according to field significance. Only a few major fields have hydrant refueling, most using trucks and hose carts.

Expansion and improvement are concentrated primarily on existing fields serving major population centers and are the direct results of increased heavy-jet traffic. Improvement includes cargo- and passenger-handling facilities, installation of hydrant refueling, and addition of new runways and taxiways. Control and navigation aids are being upgraded, but nondirectional radio beacons remain the primary facility. Extensive installation of VOR, ILS, and ASR

is planned. Thus far only Galeao, Salgado Filho, and Brasilia have ILS. The Rio de Janeiro and Sao Paulo areas have surveillance radar. Santa Cruz military is the only field having precision approach radar. An air force base to support Mirage fighters is under construction at Anapolis. Both military and joint military/civil fields have potential for expansion and support of sustained operations; however, irregular allocation of funds will probably continue to hamper progress.

Characteristics of selected airfields are listed in Figure 11.

#### K. Telecommunications (C)

The telecommunication (telecom) system compares favorably with other systems in South America but is below the standards of the United States and Western European countries. Despite extensive recent construction, most telecom facilities still are concentrated in the southern third of the country and in a relatively narrow strip of land bordering the Atlantic Ocean. Immense sections of the interior are served only by scattered radioce: munication stations and a tenuous tropospheric-scatter system. Rio de Janeiro is the dominant center of telecom services, especially in the field of international operations. The important cities of Sao Paulo, Recife, Savador, Porto Alegre, Belo Horizonte, and Brasilia continue to develop as regional centers. The trunk radio-relay system is replacing the open-wire telephone and telegraph networks as the primary traffic-carrying medium. Although nearly all modern telecom media are found in Brazil, they are not yet sufficiently developed to fulfill normal requirements of the government, the military services, and the public. The rapidly expanding population and related economic growth place constant pressures on an already overtaxed system.

Telecom facilities are owned and operated by the government and a number of private companies. Supreme authority for the administration of all telecommunications is vested in the Ministry of Communications. Two autonomous bodies, the Brazilian Telecommunications Enterprise (EMBRAT-EL) and the Brazilian Post and Telegraphs Enterprise (ECT), operate all interstate and international facilities. In addition, there are nearly 900 small telephone companies operating under state, municipal, or private ownership. Most broadcast facilities are privately owned. Both the National Telecommunications Department (DENTEL) and the National

## FIGURE 11. Selected airfields (C)

NAME AND LOCATION	LONGEST RUNWAY: SURFACE; DIMENSIONS; ELEVTION ABOVE SEA LEVFL	ESWL*	LARGEST AIRCRAFT NORMALLY SUPPORTED	REMARKS
Augusto Severo	Feei Asphalt	Pounds 56,607	C-135	Joint. Alternate for Boeing 707.
Brasilia		56,607	C-135	Joint. International airport. Civil airport, air force base.
Campo Fontenelle (Pirassununga) 21°59'S., 47°20'W.		31,000	C-118	Military. Training school for cudet pilots.
Campo Grande AB		56,607	C-135	Military. International airport.  Brazili: A Air Force and national airlines use field.
Cumbica		56,607	C-135	Military, 4th Air Zone Head- quarters.
Dois de Julho	7,621 x 150 43	48,184	C-121	Joint. One of more important fields along coast. Good refueling base. Quick turnaround. Capable of heavy-jet support.
Galeao	10,827 x 150 16	56,607	C-135	Joint. International airport. Used by USAF regularly. Complete facilities.
Gravatai	6,562 x 170 26	59,893	C-118	
Guararapes	8,205 x 161 36	56,607	C-135	Joint. International airport. Capa- ble of sustained 707 traffic.
Pampulha	Concrete	48,184	C-121	Joint. One of Brazil's better fields.  Brazilian Air Force personnel school located here.
Pinto Martins	Asphalt	56,607	C135	Joint. Sustained jet operation capability.
Ponta Pelada	Asphalt	48,184	Constellation	Civil. International airport. Primary field in Amazon Basin.
Salgado Filho	Concrete	56,607	Boeing 707	Civil. International airport. Main base for VARIG, principal airline of Brazil. Alternate for military traffic for Gravatai.
Santa Cruz	Concrete	56,607	C-135	Military. First Fighter Group sta- tioned here.
Tirirical2°35′S., 44°14′W.	Asphalt	48,184	C-121	Joint. Limited medium jet transport capability.
Val de Caes	Asphalt	56,607	C-135	Joint. International airport. Sustained jet operation capability.
Vira Copos		56,607	Boeing 707	Civil. International airport. Brazil's second largest field. Complete facilities.

<sup>\*</sup>Equivalent Single-Wheel Loading: Capacity of an airfield runway to sustain the weight of any multiple-wheel landing-gear aircraft in terms of the single-wheel equivalent.

Tel communications Council (CONTEL) function as advisory and policy making bodies.

The backbone of the domestic telecom system is a far-reaching network of interconnected high-capacity radio-relay systems and low-capacity troposphericscatter links. From dual centers in Rio de Janeiro and Sao Paulo, trunk radio-relay routes extend southwest to Curitiba and Porto Alegre, west to Campo Grande, north to Brasilia and Belem, and northeastward to Belo Horizonte and Salvador, and then along the coastline to Recife and Fortaleza. Most of these routes are operating in the 4 and 6 gigahertz (GHz) range and have ultimate capacities of 960 telephone channels and one TV channel, but current capacities are probably only a fourth of this total. Complementing the trunk routes are extensive very-high-frequency (VHF) and ultra-high-frequency (UHF) radio-relay networks in operation in most Brazilian states and having tie-ins to the national routes in the state capitals. The tropospheric-scatter network provides capacities of 69 and 120 channels and ties together widely scattered localities in northwestern Brazil from Manaus south to Campo Grande. An extensive openwire telephone network, which is carrier equipped along many important routes, is supplemented by a parallel telegraph wireline network. The old domestic radiocommunications network has been largely relegated to an emergency role. Most urban telephone systems are automatic, and increasing numbers of circuits between medium and large cities are being connected to transit switching centers to facilitate expansion of direct-distance dial operations. The number of telephones has nearly doubled since 1965 to an estimated total of 2,300,000 sets. Domestic telegraph services in the larger cities are fully automated. The telex (teleprinter-subscriber) network has about 3,500 subscribers, and there are plans to extend this service fourfold by 1976.

A wide variety of modern and increasingly automated services is available for international communications. The Intelsat satellite ground station at Tangua, 50 miles east of Rio de Janeiro, has replaced high-frequency (FIF) radiocommunications as the primary means of contact with other countries. The ground station has 106 channels in operation and has direct connections to 12 similar ground stations in the Americas and Europe. Modern HF radiocommunications originate from three sites in the Rio de Janeiro area. Most of the traffic from these stations, and from smaller installations in Manaus and Porto Alegre, is destined for Latin American countries and

the United States. Wirelines provide important links with neighboring Bolivia and Paraguay. Work on Brazil's first coaxial submarine cable is now underway; known as BRACAN-1, this cable is to carry 160 telephone channels between Recife and the Canary Islands where it will interconnect with the worldwide telephone cable system.

The general inadequacy of the public system in the past led to development of many special networks by military, industrial, and governmental organizations. The military forces operate extensive and physically separate networks. Federal and state police communication systems are constantly being expanded and modernized. Other important private systems are operated by railroad, airline, electric power, and mining companies.

Radio and TV broadcast facilities are highly developed. AM coverage is good throughout the eastern half of Brazil, but FM broadcasts are limited to larger urban centers. In mid-1973 about 900 AM and 150 FM stations were in operation. The majority of the radiobroadcast transmitters are low powered and provide programs intended for local audiences; the more powerful and influential stations are making increased use of networks to expand coverage. Extensive radio-relay routes, using circuits in newly constructed domestic systems, provide nationwide transmission of TV programs. There are 56 TV stations originating programs and about 100 additional lowpowered repeater stations. Color TV broadcasts, using the phase alternating line (PAL) system, were begun in March 1972 As of mid-1973 the number of radiobroadcast receivers was estimated at 12 million sets; the number of TV receivers, at 7 million.

The Brazilian telecom equipment industry produces all but the most sophisticated types of apparatus in quantities sufficient to meet the nation's requirements. Complete items still imported consist mainly of microwave UHF and VHF equipment, forward-scatter UHF equipment, and television transmission apparatus. However, substantial quantities of components for both wire-line and radio equipment made in Brazil continue to be imported. The principal source for wire-line components and equipment is Sweden; West Germany is a distant second. Radio equipment and components are supplied, in order of importance, by the United States, Japan, West Germany, the United Kingdom, and Italy.

Because of limited training facilities, there is a shortage of skilled labor to install and operate the many new telecom systems being constructed. EMBRATEL conducts a 5-month telecom course, and

#### Confidential

a new training center was recently opened by the Brazilian Telephone Company. Many of the personnel must acquire their knowledge and skills from on-the-job training.

Among the most important long-range plans to improve the telecom system are: 1) implementing a domestic communications satellite network in 1973-

75; 2) constructing a second antenna at the Tangua ground station for international service; 3) introducing several more high-powered AM broadcast transmitters at the *Radio Nacional* station in Brazilia; and 4) constructing high-capacity radio-relay routes into neighboring countries as part of the Inter-American Telecommunications Network.

# Glossary (u/ou)

ABBREVIATION	Portuguese	English
CELMA	Companhia Electro mecanica	
CMEF	Companhia Mojiana de Estradas de Ferro	Mogiana Railroad Company
CMM		Merchant Marine Commission
CONTEL		National Telecommunications Coun-
CPEF	Companhia Paulista de Estradas de Ferro	Paulista Railroad Company
CRUZEIRO	Servicos Aereos Cruzeiro do Sul S.A	
DENTEL		National Telecommunications De- partment
DER	Departamento de Estradas de Rodagem	State Highway Department
DNEF	Departamento Nacional de Estradas de Ferro	National Railroad Department
DNER	Departamento Nacional de Estradas de Rodagem	National Highway Department
DNPVN	Departamento Nacional de Portos e Vias Navegaveis	National Department of Ports ad Navigable Routes
ECT		Brazilian Post and Telegraphs Enter- prise
EFA	Estrada de Ferro Araraquara	Araraquara Railroad
EFAP	Estrada de Ferro 🖰 Amapa	Amapa Railroad
EFCJ	Estrada de Ferro Campo do Jordao	Campos do Jordao Railroad
EFMM	Estrada de Ferro Madeira Mamore	Madeira Mamore Railroad
EFPP	Estrada de Ferro Perus-Pirapora	Perus-Pirapora Railroad
EFS	Estrada de Ferro Sorocabana	Sorocabana Railroad
EFSPM	Estrada de Ferro Sao Paulo e Minas	Sao Paulo and Minas Railroad
EFT	Estrada de Ferro Tocantins	Tocantins Railroad
EFV	Estrada de Ferro Votorantim	Votorantim Railroad
EFVM	Estrada de Ferro Vitoria a Minas	Vitoria to Minas Railread
EMBRATEL	Empresa Brasileira de Tele- comunicacoes	Brazilain Telecommunications Enter- prise
FEPASA	Ferrovia Paulista, S.A	Sao Paulo Railroad Corp.
FM M		Merchant Marine Fund
FRONAPE	Frota Nacional de Petroleos	
GEIPOT	Grupo de Estudas Para Integração de Política de Transports	
PF FROBRAS	Petroleo Brasileiro	
REESA	Rede Ferroviaria Federal, S.A	Federal Railroad Network, Inc.
SADIA	SADIA S.A. Transportes Acrees	
8RC	Sistema Regional Centro	Central Regional System
SRN	Sistema Regional Nordeste	Northeast Regional System
SRP	Sistema Regional Centro-Sul	South-Central Regional System
SRS	Sistema Regional Sul	Southern Regional System National Merchant Marine Super-
VARIG	Empresa de Viacao Aereo Rio-	intendency
VASP	Grandense, S.A. Viacao Aerea Sao Paulo, S.A	

36


NO FOREIGN DISSEM


CONFIDENTIAL

## Places and features referred to in this General Survey (u/ou)

	COORDINATES		res			coorb	1 N A 1	res		
	۰	'S.	۰	'W.					/ W	
Abuña	9	42	65	23	Itajaí	96	5 53		39	Rio Itapicuru (stream)
Magoinhas	12	07	38	26	Itapetininga				03	Rio Jacuí (stream)
Alemôa	23	56	46	22	Itapetinga	1.5	15		15	11
Megrete	29	46	55	46	Itararé	94	10			Rio Jaguarão (stream)
Amazon Basin (drainage basin)	2	30	60	00	Itirapina	24	07		20	Rio Jequitinhonha (stream)
imazonia (region)	- 4	00	60	00	Jacarepaguá	22	: 15		49	Rio Largo
Amazon River (stream)		10	49	00	Jaguaribe	22	. 55		21	Rio Madeira (stream)
Angra dos Reis		00	44		Japeri	7	08		53	Rio Mearim (stream)
gua Grande (oilfield)			38	•	João Pessoa.	22	39		40	Rio Mucuri (stream)
Arneaju			37		Juàzeiro	7			52	Rio Negro (stream)
Araguari			48		luis de Fore	9	25		30	Rio Pará (distributary)
Taranguá			49		Juiz de Fora	21	45		20	Rio Paraguaçu (stream)
raraquara			48		Jundiaí	23	3 11	46	52	Rio Paraguai (stream)
ıratu			38		Jupiá (rr sta)	20	47	51	39	Rio Paraíba (stream)
raxá	_				Ladário	19	01	57	35	Rio Paraíba do Sul (stream)
			46		Lagon dos Patos (lagonn)	31	-06	51	15	Rio Paraná (stream)
reia Branca		57	37		Lagoa Mirim	32	45	52	50	Rio Paraopeba (stream)
rtigas, Uruguay			56		Lajes	27	48	50	19	Rio Pardo (stream)
sunción, Paraguay			57		Lavras	21	14	45	00	Rio Parnaíba (stream)
talaia Velha			37	04	Lídice	22	2 51	44	12	Rio Purus (stream)
saía de Guanabara (bay)			43	10	Luís Correia	2	2 53	41	40	Rio Quaraí (stream)
Bariri			48	44	Maceió	ą	40	35	43	Rio São Francisco (stream)
arra Bonita			48	32	Madre de Deus	12	2 44	38	37	Rio Tapajós (stream)
arra do Piraí	22	28	43	49	Manaus		3 08	60	01	Rio Taquari (stream)
	-		-		Manhara	-96	15	-49	02_	Pio Tief & (etregen)

ATES		¢	OORD	1:4A1	res
'W.			'S.	۰	'W.
<b>B</b> 39	Rio Itapicuru (stream)	2	52	44	12
8 03	Rio Jacuí (stream)	30	02	51	15
0 15 9 20 7 49	Rio Jaguarão (stream)	32	39	53	12
9 20	Rio Jequitinhonha (stream)	15	51	38	53
	Rio Largo	9	29	35	51
<b>3</b> 21	Rio Madeira (stream)	3	22	58	45
4 53	Rio Mearim (stream)		04	44	35
8 40	Rio Mucuri (stream)	• 3	05	39	34
4 52 0 30	Rio Negro (stream)	3	: :	59	55
<b>0</b> 30	Rio Pará (distributary)	1	40	49	15
3 20	Rio Paraguacu (stream)		45	38	54
6 52 1 39	Rio Paraguai (stream)	27	18	58	38
1 39	Rio Paraíba (stream)		58	34	51
7 35	Rio Paraíba do Sul (stream)	21	37	41	03
1 15	Rio Paraná (stream)			59	15
<b>2</b> 50	Rio Paraopeba (stream)			45	11
0 19	Rio Pardo (stream)			38	57
<b>8</b> 00	Rio Parnaíba (stream)	3	00	41	50
4 12	Rio Purus (stream)	. 1	54	53	29
1 40	Rio Quaraí (stream)	30	12	57	36
<b>5</b> 43	Rio São Francisco (stream)	. 10	30	36	24
8 37	Rio Tapajós (stream)		24		41
<b>60</b> (01	Rio Taquari (stream)				17
oa	Die Tieth (elreges)	_20	40	_51	35





APPROVED FOR RELEASE: 2009/06/16:	CIA-RDP01-00707R000200080021-4

Barragem de Boa Esperança (dam)					
Barra Mansa				11	Mapele
Barreiro (rr sta)				02	Marcellio Kallos
Barueri				53	20 23 43 25 Rivera, Uruguay
Bauru			49	29	29 42 51 58   Roncador
Belém					Mataripe
Belo Horizonte			40 51	56 56	
Bom Retiro do Sul					Mogi das Cruzes
Botelho				46	
Botucatu				26	
Brasília				55	1
Buenos Aires, Argentina			58		Mucuripe
Buracica (oilfield)				24	Natal 5 47 35 13 Santa Maria
Cabedelo				50	Niterói
Cabo				02	Nova Era
Cabrália Paulista				20	Nova Iguaçu
Cacequi				49	Oiticica
Cachimbo				54	Olinda
Caioba (oilfield)				33	Osasco (rr sla)
Camaçari				12	Osório
Camaquã				49	Ouro Préto
Camocit				50	Panorama
Campinas				05	Paraíba do Sul
Campo Grande				37	Paranaguá
Canal de São Gonçalo (navigational canal).				38	Paranapiacaba
Candeias (oilfield)	12	42		33	Paso de los Libres, Argentina 29 43 57 05 São Francisco do Sul
Capuava				58	Paula Cavalcante (rr sta)
Carinópolis				59	Paulínia 22 45 47 10   São Luís
Caratinga	19	47	42	08	Paulista 7 57 34 53   São Paulo
Catalão	18	10	47	57	Paulistana 8 09 41 09 São Sebastião
Chui	33	4 i	53	27	Pelotas 31 46 52 20   Sepetiba (bay)
Colômbia	20	10	48	40	Petrópolis
Congonhas	20	30	43	52	Piaçabuçu 10 24 36 25   Sorocaba
Conselheiro Lafaiete	20	40		48	Piassaguera (rr sta)
Corumbá	19	01	57	39	Piedade, Serra da (ridge)
Coxilha de Santa	31	15	55	15	Pirapora 17 21 44 56 Taquipe (oilfield)
Cubatão	23	53	46	25	Pirassununga
Cuiabá	15	35	56	05	Poços de Caldas
Curitiba	25	25	49	15	Ponta Grossa
Diamantina	18	15	43	36	Portão (rr sta)
Divinópolis	20	09	44	54	Pôrto Alegre
Dom João (oilfield)	12	37	38	39	Pôrto Esperança
Doutor Joaquim Murtinho (rr sta)	20	33	43	49	Pôrto Flores
Daque de Caxias	22	47	43	18	Pôrto Mendes 24 30 54 20 Utinga (rr sta)
Engenheiro Bley	25	37	49	45	Pôrto Passagem (rr sta)
Entroncamento			54	56	Pôrto Real do Colégio 10 11 36 49 Vassouras
Exu	7	31	39	43	Pôrto União
Fernandes Pinheiro				13	Pôrto Velho
Ferrugem (rr sta)				01	Pôrto Xavier
Florianópolis			48	34	Presidente Epitácio
Fortaleza				30	Propriá 10 13 36 51
Foz do Iguaçu				35	Promissao (dam)
Garças de Minas (rr sta)				40	Quaraí
General Luz (rr sta)			51	22	
Goiânia				16	ll b
Guaira				15	plasma,
Guaratinguetá				13	n   campo contenene (1)
Guarulhos				32	The state of the s
Horto Florestal (rr sta)				55	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Ibirarema.				06	l sois de sumo
Ibitinga				59	\taleno, \
liha d'Água (14)				10	little to the transfer of the
Ilha do Barnabé (isl)				20	nia da tamaina
Ilha do Governador (isl)				12	Die de la Dieta Argentina (estrory)
Dhéus				03	Die Deservations de l'internation de l'i
				40	Touto relaca
Imbituba	,			12	ni da
Imbituba	22	()))			7 Same ( Manage )
Ipanema, Praia de					vanta cruz
Ipanema, Praia de	23	21	47	41	Rio Gurupi (stream)
Ipanema, Praia de	23 7	21 20	47 35		vanta cruz

### APPROVED FOR RELEASE: 2009/06/16: CIA-RDP01-00707R000200080021-4

			THE REPORT OF THE PERSON OF TH		. 18	*
	Mapele	8 26	Rio Tocantins (stream)	Ç.	£.	
	Marcelino Ramos	1 54			49	
	Mariana	3 25	Rivera, Uruguay	36	45	19
	Mariante	1 58	Roncador 17	54 .	55	
	Mataripe	8 35	Rubião Júnior (rr sta)	22 4	48	
L	Miranga (oilfield) 12 23 36	8 11	Rubinéia	53 4	48	
	Mogi das Cruzes	3 11			51 (	
	Monte Azul	2 53	Saito das Sete Quedas (waterfall)		39 (	_
	Montevideo, Uruguay	11	Salvador		54	
	Mossoró	20	Santa Cruz		38 ;	
	Mucuripe	29	Santa Cruz, Bolivia		3 4	
	Natal	13	Santa Maria	8 6	3 1	
	Niterój	07	Santa Maria da Boa Vista.	0 0	3 4	
	NOV9 Immen	03	Santana do Livramento.	9 . 9 .	9 4 5 3	
		27	Santarem		o 3 44	
	Ulings	05	Santarem		1 1 5 0	_
ı	USBSCO (rr ele)		Santiago, Chile			-
H	USOPIO		Santo Amaro		0 4	
H	Ouro Prêto 29 54 50		Santo Amaro do Sul		8 4	
	Ouro Prêto     20 23 43       Panorama     21 21 51	-	Bantos	•	15 52	
1	raraine do Sul		Bao Bernardo do Campo 92 44		o 20 3 3:	-
ı			Sao Castano do Sul		34	_
ı			Sau Francisco (rr stg)		25	
ı	Paso de los Libros Argontino		Sao Francisco (drainage hasin) 10 no			
	Paso de los Libres, Argentina.       29 43 57 (         Paula Cavalcante (rr sta).       7 09 35 (		Sao Francisco do Sul.	36 40	24	
			Sao Jose dos Campos		39	
1			Sao Luis		53 16	
	Paulistono	- 1	Sao Paulo			
ı		- 4	Sau Sepastiao		37	
1	Petrópolis 31 46 52 2		Depetina (oay)		25	
ı	Petrópolis		SOUTH		48	
1	Piaçabuçu     10 24 36 2       Piassaguera (rr sta)     23 50 46 2	- 11	SOFOCADA	40		
	Pledade Sorre de /-id)		Bousa	47		
	'iranore _	- 11	rangua	38		
L	1179 88110 110 000	- 11	raquipe (oithield)	42		
h	OCOS de Caldas		reresina	38		
ı	Onta Groveo	4	I ramandai.	42		
L	Oftao (rr eta)	' #	Tiva Corações.	50		
ı		· II	1100 11100	45		
ı	Octo Esparance	. 11	Tubana,	43		
ī	Ofto Flores	II .	Crugualana.	40 ± 57 (		
F	Orio Mandos	· 11	oraguay River (stream)	58 1		
P	Ofto Passagom (== oto)	' (	Conga (rr sta)			
P	Otto Roal do Colúmia	. 11	varue-Ches	46 3	_	
P	Otto Linião	11	vassouras.	48 2		
P	Orto Valho	И	Trada Noiva (rr sia)	43 4		
P	Orto Xavior	- 0	the attition	48 5	-	
P	regidente Unitérie	, JI '	ricolla	43 2	-	
P	ronria		Volta Redonda	40 2		
P	ODISSO (dam)	- 1	22 32	44 0	1	
Q	larai	1	Soloni- L. etc.			
Ř	ecife	1	Selected airfields			
R	CODCOVO (basis)	A	ugusto Severo	20		
R	PCFEIO	11 17	IASINA	35 15		
R	esende	11 `	ampo rontenelle (Pirassinungo) or so	47 55		
R	heira	11	ampo Grande AB	47 20		
Ri	DCÃO	11 `	untoica	54 40		
Ri	0 ACH (storam)	" "	ois de Juino,	46 29		
Ri		11 11	arcao	38 20		
Rí	Branco Licuguay	11	avatal	43 15		
Ri	) de Janeiro	11	uararapes	51 08		
Rí	de la Plata Argentina (t	1.8	impuina	34 55		
Ri	Doce (stream)	Pi	neo wartins	3 57		
Ric	Grande	Po	ato relada	38 32		
Ri	Guaiba (cstuary)	Sa	igado Filho.	9 59		
Ri-	Gurupi (stream)	Sa		1 10		
₹i.	Thicui (etream)	Tir	HICAL	3 43		
lie	Itaiaí (elream)	Va	i de Caes	4 14		
	Teajai (************************************	Vir	a Copos.	8 33		
			23 00 4	7 18	_	
:						

Tropic of C ( Central

